

屋内照明器具特性

品番 (品名)	LGW40100	
光源	LLD3020LCE1 ×1	795.0 lm
管理番号	K0176345 (0) DR 1	
BZ分類	BZ1	

器具効率	89%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	89%	床	10%				10%				10%				10%				0%		
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	cm ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0										
	等価発光面積		cm ²	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0										
取付高さ	器具間隔最大限																				
	横方向 (A)	縦方向 (B)																			
Hm	0.41Hm	0.41Hm	4.0	5.0	7.0	10.0															

