

屋内照明器具特性

| | | |
|---------|---|-----------|
| 品番 (品名) | L G W 4 0 2 0 0 | |
| 光源 | LLD40001CQ1 ×1 | 845.0 l m |
| 管理番号 | K0176343 (0) DR 1 | |
| B Z 分類 | B Z 3 / 0 . 9 / B Z 2 / 4 . 5 / B Z 3 / 6 . 0 / B Z 2 | |

| | | | | | | | | | | | | | | | | | | | | | |
|--------|-------------------|-----------|--------------|-----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|----|-------|
| 器具効率 | 58 % | 天井 | 80 % | | | | 70 % | | | | 50 % | | | | 30 % | | | | 0 % | | |
| | 上方光束 0 % | | 下方光束 58 % | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0 % |
| 室指数 | 照明率 (X 0 . 0 1) | | | | | | | | | | | | | | | | | | | | Z C M |
| 保守率 | 良 | 0.63 | 0.6 | 37 | 31 | 28 | 25 | 37 | 31 | 27 | 25 | 36 | 31 | 27 | 25 | 35 | 30 | 27 | 25 | 24 | |
| | 中 | 0.6 | 0.8 | 43 | 38 | 34 | 32 | 43 | 38 | 34 | 32 | 41 | 37 | 34 | 31 | 40 | 36 | 33 | 31 | 30 | |
| | 否 | 0.56 | 1.0 | 47 | 42 | 39 | 36 | 46 | 42 | 39 | 36 | 45 | 41 | 38 | 36 | 44 | 40 | 38 | 36 | 35 | |
| | | | 1.25 | 50 | 46 | 43 | 40 | 50 | 46 | 43 | 40 | 48 | 45 | 42 | 40 | 47 | 44 | 42 | 40 | 39 | |
| 下方投影面積 | c m ² | | 1.5 | 52 | 49 | 46 | 43 | 52 | 48 | 45 | 43 | 50 | 47 | 45 | 43 | 49 | 46 | 44 | 42 | 41 | |
| 等価発光面積 | c m ² | | 2.0 | 55 | 52 | 49 | 47 | 54 | 51 | 49 | 47 | 53 | 50 | 48 | 47 | 51 | 49 | 48 | 46 | 45 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 56 | 54 | 52 | 50 | 56 | 53 | 51 | 50 | 54 | 52 | 51 | 49 | 53 | 51 | 50 | 48 | 47 | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 58 | 55 | 53 | 52 | 57 | 55 | 53 | 51 | 55 | 54 | 52 | 51 | 54 | 53 | 51 | 50 | 49 | |
| H m | 1.17 H m | 1.17 H m | 4.0 | 59 | 57 | 56 | 54 | 58 | 57 | 55 | 54 | 57 | 55 | 54 | 53 | 55 | 54 | 53 | 52 | 51 | |
| | | | 5.0 | 60 | 58 | 57 | 56 | 59 | 58 | 56 | 55 | 57 | 56 | 55 | 54 | 56 | 55 | 54 | 54 | 52 | |
| | | | 7.0 | 60 | 59 | 58 | 58 | 60 | 59 | 58 | 57 | 58 | 58 | 57 | 56 | 57 | 56 | 56 | 55 | 54 | |
| | | | 10.0 | 61 | 60 | 60 | 59 | 60 | 60 | 59 | 58 | 59 | 58 | 58 | 57 | 58 | 57 | 57 | 56 | 55 | |

