

屋内照明器具特性

品番 (品名)	L G W 4 0 2 0 0	
光源	LLD20001CQ1 ×1	531.0 lm
管理番号	K0176344 (0) DR 1	
B Z 分類	B Z 3 / 0 . 9 / B Z 2 / 4 . 5 / B Z 3 / 6 . 0 / B Z 2	

器具効率	58 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		0 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		58 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X 0 . 0 1)																				Z C M
保守率	良	0.63	0.6	3.8	3.2	2.8	2.5	3.7	3.1	2.8	2.5	3.6	3.1	2.7	2.5	3.5	3.0	2.7	2.5	2.4	
	中	0.6	0.8	4.4	3.8	3.5	3.2	4.3	3.8	3.4	3.2	4.2	3.7	3.4	3.2	4.0	3.7	3.4	3.2	3.0	
	否	0.56	1.0	4.7	4.3	3.9	3.7	4.7	4.2	3.9	3.6	4.5	4.1	3.8	3.6	4.4	4.1	3.8	3.6	3.5	
	下方投影面積	c m ²		1.25	5.1	4.6	4.3	4.1	5.0	4.6	4.3	4.1	4.8	4.5	4.2	4.0	4.7	4.4	4.2	4.0	3.9
等価発光面積	c m ²		1.5	5.3	4.9	4.6	4.4	5.2	4.8	4.6	4.3	5.0	4.7	4.5	4.3	4.9	4.6	4.4	4.3	4.1	
	c m ²		2.0	5.5	5.2	5.0	4.8	5.5	5.2	4.9	4.7	5.3	5.1	4.9	4.7	5.2	5.0	4.8	4.6	4.5	
取付高さ	器具間隔最大限		2.5	5.7	5.4	5.2	5.0	5.6	5.4	5.2	5.0	5.5	5.3	5.1	4.9	5.3	5.2	5.0	4.9	4.7	
	横方向 (A)	縦方向 (B)	3.0	5.8	5.6	5.4	5.2	5.7	5.5	5.3	5.2	5.6	5.4	5.2	5.1	5.4	5.3	5.2	5.0	4.9	
H m	1.17 H m	1.17 H m	4.0	5.9	5.8	5.6	5.5	5.8	5.7	5.5	5.4	5.7	5.6	5.5	5.3	5.6	5.5	5.4	5.3	5.1	
			5.0	6.0	5.9	5.7	5.6	5.9	5.8	5.7	5.6	5.8	5.7	5.6	5.5	5.7	5.6	5.5	5.4	5.3	
			7.0	6.1	6.0	5.9	5.8	6.0	5.9	5.8	5.7	5.9	5.8	5.7	5.7	5.7	5.7	5.6	5.6	5.4	
			10.0	6.2	6.1	6.0	5.9	6.1	6.0	6.0	5.9	5.9	5.9	5.8	5.8	5.8	5.8	5.7	5.7	5.5	

