

屋内照明器具特性	
品番 (品名)	XAD11012K
光源	LLD20002CQ1 ×1 531.0 lm
管理番号	K0175548 (0) DR1
BZ分類	BZ4/0.7/BZ3

器具効率		64 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z
保守率		良 中 否	0.67	0.6	39	32	27	24	38	31	27	24	37	31	27	24	35	30	26	24	23
			0.63	0.8	46	39	35	31	45	39	34	31	43	38	34	31	42	37	34	31	30
			0.56	1.0	50	44	40	37	49	44	40	37	47	43	39	36	46	42	39	36	35
				1.25	54	49	45	42	53	48	44	41	51	47	44	41	50	46	43	41	39
下方投影面積		cm ²		1.5	56	52	48	45	55	51	48	45	54	50	47	44	52	49	46	44	43
			等価発光面積	cm ²	2.0	59	56	52	50	59	55	52	50	57	54	51	49	55	53	50	49
取付 高さ	器具間隔最大限			2.5	61	58	55	53	60	58	55	53	59	56	54	52	57	55	53	52	50
	横方向 (A) 縦方向 (B)			3.0	63	60	58	55	62	59	57	55	60	58	56	54	59	57	55	54	52
H m	1.25 H m 1.25 H m			4.0	64	62	60	58	63	61	60	58	62	60	59	57	60	59	58	56	55
				5.0	65	64	62	60	64	63	61	60	63	61	60	59	61	60	59	58	56
				7.0	66	65	64	63	66	64	63	62	64	63	62	61	63	62	61	60	58
				10.0	67	66	65	65	66	66	65	64	65	64	64	63	63	63	62	62	60

