

屋内照明器具特性

品番 (品名)	NNLK41109 + NNL4500KNT	
光源	LED5000_85_4550 ×1	4550.0 lm
管理番号	K0144286 (0) DB1	
BZ分類	BZ4 / 6.0 / BZ5	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		10%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		90%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.83	0.6	58	47	40	35	57	46	39	34	53	44	38	34	50	43	37	33	30	
	中	0.81	0.8	68	58	50	45	66	56	50	45	62	54	48	44	59	52	47	43	40	
	否	0.77	1.0	75	65	58	53	72	63	57	52	68	61	55	51	65	58	53	49	46	
			1.25	80	71	65	60	78	70	64	59	74	67	62	57	70	64	60	56	52	
下方投影面積	c m ²		1.5	84	76	70	65	82	74	68	64	77	71	66	62	73	68	64	60	57	
	等価発光面積		c m ²	2.0	89	82	77	72	87	80	75	71	82	77	73	69	78	74	70	67	63
取付高さ	器具間隔最大限		2.5	92	86	81	77	90	84	80	76	85	81	77	74	81	77	74	71	67	
	横方向 (A)	縦方向 (B)	3.0	94	89	85	81	92	87	83	80	87	83	80	77	83	80	77	75	70	
1.5m	1.95m	2.04m	4.0	97	93	89	86	95	91	88	85	90	87	84	82	86	83	81	79	74	
2	2.58	2.58	5.0	99	95	92	89	96	93	90	88	92	89	87	85	87	85	83	82	77	
2.5	3.21	3.15	7.0	101	98	96	94	98	96	94	92	94	92	90	88	89	88	86	85	80	
3	3.84	3.72	10.0	102	100	99	97	100	98	96	95	95	94	93	91	91	90	89	88	82	

