

| 屋内照明器具特性 |                            |
|----------|----------------------------|
| 品番 (品名)  | XAD3 1 0 0 K               |
| 光源       | LLD3 0 0 0 CU1 ×1 795.0 lm |
| 管理番号     | K0178931 ( 0 ) DR 1        |
| BZ分類     | BZ4 / 1.4 / BZ3            |

| 器具効率     |                   | 88 %            | 反射率    | 天井              | 80 %              |    |    |    |    | 70 % |    |    |    |    | 50 % |    |    |    |    | 30 % |     |    |  |  | 0 % |
|----------|-------------------|-----------------|--------|-----------------|-------------------|----|----|----|----|------|----|----|----|----|------|----|----|----|----|------|-----|----|--|--|-----|
|          |                   |                 |        | 壁               | 70                | 50 | 30 | 10 | 70 | 50   | 30 | 10 | 70 | 50 | 30   | 10 | 70 | 50 | 30 | 10   | 0 % |    |  |  |     |
|          |                   |                 |        | 床               | 10 %              |    |    |    |    | 10 % |    |    |    |    | 10 % |    |    |    |    | 10 % |     |    |  |  | 0 % |
|          |                   |                 |        | 室指数             | 照明率 ( X0.01 ) ZCM |    |    |    |    |      |    |    |    |    |      |    |    |    |    |      |     |    |  |  |     |
| 保守率      |                   | 良<br>中<br>否     | 0.67   | 0.6             | 53                | 43 | 36 | 32 | 52 | 42   | 36 | 32 | 50 | 41 | 36   | 32 | 48 | 40 | 35 | 31   | 30  |    |  |  |     |
|          |                   |                 | 0.63   | 0.8             | 62                | 53 | 46 | 42 | 61 | 52   | 46 | 42 | 59 | 51 | 45   | 41 | 56 | 50 | 45 | 41   | 39  |    |  |  |     |
|          |                   |                 | 0.56   | 1.0             | 68                | 59 | 53 | 49 | 67 | 59   | 53 | 49 | 64 | 57 | 52   | 48 | 62 | 56 | 52 | 48   | 46  |    |  |  |     |
|          |                   |                 |        | 1.25            | 73                | 66 | 60 | 56 | 72 | 65   | 60 | 55 | 69 | 63 | 59   | 55 | 67 | 62 | 58 | 55   | 53  |    |  |  |     |
| 下方投影面積   |                   | cm <sup>2</sup> |        | 1.5             | 77                | 70 | 65 | 60 | 75 | 69   | 64 | 60 | 73 | 68 | 63   | 60 | 71 | 66 | 62 | 59   | 57  |    |  |  |     |
|          |                   |                 | 等価発光面積 | cm <sup>2</sup> | 2.0               | 81 | 76 | 71 | 68 | 80   | 75 | 71 | 67 | 78 | 73   | 70 | 66 | 75 | 72 | 68   | 66  | 64 |  |  |     |
| 取付<br>高さ | 器具間隔最大限           |                 |        | 2.5             | 84                | 79 | 76 | 72 | 83 | 79   | 75 | 72 | 80 | 77 | 74   | 71 | 78 | 75 | 72 | 70   | 68  |    |  |  |     |
|          | 横方向 (A) 縦方向 (B)   |                 |        | 3.0             | 86                | 82 | 79 | 76 | 85 | 81   | 78 | 75 | 82 | 79 | 76   | 74 | 80 | 78 | 75 | 73   | 71  |    |  |  |     |
| H m      | 1.25 H m 1.25 H m |                 |        | 4.0             | 88                | 85 | 82 | 80 | 87 | 84   | 82 | 79 | 85 | 82 | 80   | 78 | 83 | 81 | 79 | 77   | 75  |    |  |  |     |
|          |                   |                 |        | 5.0             | 90                | 87 | 85 | 83 | 89 | 86   | 84 | 82 | 86 | 84 | 82   | 81 | 84 | 83 | 81 | 80   | 77  |    |  |  |     |
|          |                   |                 |        | 7.0             | 91                | 89 | 88 | 86 | 90 | 88   | 87 | 85 | 88 | 87 | 85   | 84 | 86 | 85 | 84 | 82   | 80  |    |  |  |     |
|          |                   |                 |        | 10.0            | 93                | 91 | 90 | 89 | 91 | 90   | 89 | 88 | 89 | 88 | 87   | 86 | 87 | 86 | 86 | 85   | 82  |    |  |  |     |

