

|          |                                 |
|----------|---------------------------------|
| 屋内照明器具特性 |                                 |
| 品番 (品名)  | LGB15041BF                      |
| 光源       | LDA7L-D-G/S/Z6 ×1      810.0 lm |
| 管理番号     | K0126485(0)DB1                  |
| BZ分類     | BZ8                             |

|        |                 |         |             |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|-----------------|---------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 91%             | 天井      | 80%         |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|        |                 |         | 壁           | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
| 上方光束   | 38%             | 反射率     | 10%         |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |     |
| 下方光束   | 53%             |         | 床           | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |
|        |                 | 室指数     | 照明率 (X0.01) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |     |
| 保守率    | 良               | 0.63    | 0.6         | 4.2 | 3.0 | 2.3 | 1.8 | 3.8 | 2.8 | 2.2 | 1.7 | 3.3 | 2.4 | 1.9 | 1.5 | 2.7 | 2.1 | 1.6 | 1.2 | 8   |
|        | 中               | 0.6     | 0.8         | 4.9 | 3.8 | 3.0 | 2.5 | 4.6 | 3.5 | 2.8 | 2.3 | 3.9 | 3.0 | 2.5 | 2.0 | 3.2 | 2.6 | 2.1 | 1.7 | 1.2 |
|        | 否               | 0.56    | 1.0         | 5.5 | 4.4 | 3.6 | 3.0 | 5.0 | 4.1 | 3.4 | 2.8 | 4.3 | 3.5 | 2.9 | 2.5 | 3.6 | 3.0 | 2.5 | 2.1 | 1.5 |
|        |                 |         | 1.25        | 6.0 | 5.0 | 4.2 | 3.6 | 5.5 | 4.6 | 3.9 | 3.4 | 4.7 | 4.0 | 3.4 | 3.0 | 3.9 | 3.4 | 2.9 | 2.5 | 1.8 |
| 下方投影面積 | cm <sup>2</sup> | 1.5     | 6.3         | 5.4 | 4.6 | 4.1 | 5.9 | 5.0 | 4.4 | 3.8 | 5.0 | 4.3 | 3.8 | 3.3 | 4.2 | 3.7 | 3.2 | 2.9 | 2.1 |     |
| 等価発光面積 |                 | 2.0     | 6.8         | 6.0 | 5.3 | 4.8 | 6.3 | 5.6 | 5.0 | 4.5 | 5.4 | 4.8 | 4.3 | 3.9 | 4.6 | 4.1 | 3.7 | 3.4 | 2.5 |     |
| 取付高さ   | 器具間隔最大限         |         | 2.5         | 7.2 | 6.4 | 5.8 | 5.3 | 6.7 | 6.0 | 5.5 | 5.0 | 5.7 | 5.2 | 4.7 | 4.4 | 4.8 | 4.4 | 4.1 | 3.7 | 2.8 |
|        | 横方向 (A)         | 縦方向 (B) | 3.0         | 7.4 | 6.8 | 6.2 | 5.7 | 6.9 | 6.3 | 5.8 | 5.4 | 5.9 | 5.5 | 5.1 | 4.7 | 5.0 | 4.7 | 4.3 | 4.0 | 3.0 |
| Hm     | 1.50Hm          | 1.50Hm  | 4.0         | 7.7 | 7.2 | 6.7 | 6.3 | 7.2 | 6.7 | 6.3 | 5.9 | 6.2 | 5.8 | 5.5 | 5.2 | 5.3 | 5.0 | 4.7 | 4.5 | 3.4 |
|        |                 |         | 5.0         | 7.9 | 7.5 | 7.0 | 6.6 | 7.4 | 7.0 | 6.6 | 6.3 | 6.4 | 6.1 | 5.8 | 5.5 | 5.5 | 5.2 | 5.0 | 4.8 | 3.6 |
|        |                 |         | 7.0         | 8.2 | 7.8 | 7.5 | 7.1 | 7.7 | 7.3 | 7.0 | 6.7 | 6.7 | 6.4 | 6.1 | 5.9 | 5.7 | 5.5 | 5.3 | 5.1 | 3.9 |
|        |                 |         | 10.0        | 8.4 | 8.1 | 7.8 | 7.6 | 7.9 | 7.6 | 7.4 | 7.1 | 6.9 | 6.7 | 6.5 | 6.3 | 5.9 | 5.8 | 5.6 | 5.5 | 4.2 |

