

屋内照明器具特性	
品番 (品名)	LGB19335WZ
光源	LDA7L-D-G/S/Z6 ×3      810.0 lm
管理番号	K0172632(0)DB1
BZ分類	BZ10

器具効率	80%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	38%	室指数	床	10%				10%				10%				10%				0%
下方光束	42%		照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	3.4	2.4	1.7	1.3	3.1	2.2	1.6	1.2	2.6	1.8	1.3	1.0	2.0	1.5	1.0	0.7	0.3
	中	0.6	0.8	4.1	3.1	2.4	1.9	3.7	2.8	2.2	1.7	3.1	2.3	1.8	1.4	2.5	1.9	1.5	1.1	0.6
	否	0.56	1.0	4.6	3.6	2.9	2.3	4.2	3.3	2.6	2.1	3.4	2.7	2.2	1.8	2.7	2.2	1.8	1.4	0.8
			1.25	5.0	4.1	3.4	2.8	4.6	3.7	3.1	2.6	3.8	3.1	2.6	2.2	3.0	2.5	2.1	1.8	1.1
下方投影面積		cm <sup>2</sup>	1.5	5.3	4.5	3.8	3.2	4.9	4.1	3.5	3.0	4.0	3.4	2.9	2.5	3.3	2.8	2.4	2.1	1.3
等価発光面積		cm <sup>2</sup>	2.0	5.8	5.0	4.4	3.9	5.3	4.6	4.1	3.6	4.4	3.9	3.4	3.0	3.6	3.2	2.8	2.5	1.6
取付高さ	器具間隔最大限		2.5	6.1	5.4	4.8	4.3	5.6	5.0	4.5	4.0	4.7	4.2	3.8	3.4	3.8	3.5	3.1	2.8	1.9
	横方向 (A)	縦方向 (B)	3.0	6.3	5.7	5.2	4.7	5.8	5.3	4.8	4.4	4.9	4.5	4.1	3.7	4.0	3.7	3.4	3.1	2.1
Hm	2.55Hm	2.51Hm	4.0	6.6	6.1	5.6	5.2	6.1	5.7	5.2	4.9	5.2	4.8	4.5	4.2	4.3	4.0	3.7	3.5	2.4
			5.0	6.8	6.4	6.0	5.6	6.3	5.9	5.5	5.2	5.4	5.0	4.7	4.5	4.4	4.2	4.0	3.7	2.6
			7.0	7.1	6.7	6.4	6.1	6.6	6.2	5.9	5.7	5.6	5.3	5.1	4.9	4.7	4.5	4.3	4.1	2.9
			10.0	7.3	7.0	6.7	6.5	6.7	6.5	6.3	6.0	5.8	5.6	5.4	5.2	4.9	4.7	4.5	4.4	3.2

