

# 屋内照明器具特性

|         |   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|---|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XLX406EENJ                              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_6720 x1 6720.0 lm            |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0144565 (3) DB1                        |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ5/1.4/BZ4/2.3/BZ5/2.8/BZ4<br>/3.5/BZ5 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                  |         |      |                 |     |     |     |     |     |     |     |     |    |    |     |     |    |    |    |    |
|--------|------------------|---------|------|-----------------|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|-----|----|----|----|----|
| 器具効率   | 100%             | 天井      | 80%  |                 |     |     | 70% |     |     |     | 50% |     |    |    | 30% |     |    |    | 0% |    |
|        |                  |         | 壁    | 70              | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10 | 0% |
| 上方光束   | 0%               | 反射率     | 床    | 10%             |     |     |     | 10% |     |     |     | 10% |    |    |     | 10% |    |    |    | 0% |
| 下方光束   | 100%             |         | 室指数  | 照明率 (X0.01) ZCM |     |     |     |     |     |     |     |     |    |    |     |     |    |    |    |    |
| 保守率    | 良<br>中<br>否      | 0.77    | 0.6  | 57              | 45  | 38  | 32  | 56  | 45  | 37  | 32  | 54  | 44 | 37 | 32  | 52  | 43 | 37 | 32 | 30 |
|        |                  | 0.72    | 0.8  | 67              | 56  | 48  | 43  | 66  | 55  | 48  | 43  | 63  | 54 | 47 | 42  | 61  | 53 | 47 | 42 | 40 |
|        |                  | 0.68    | 1.0  | 74              | 64  | 56  | 50  | 73  | 63  | 56  | 50  | 70  | 61 | 55 | 50  | 67  | 60 | 54 | 49 | 47 |
|        |                  |         | 1.25 | 80              | 71  | 63  | 58  | 78  | 70  | 63  | 58  | 75  | 68 | 62 | 57  | 73  | 66 | 61 | 57 | 54 |
| 下方投影面積 | c m <sup>2</sup> | 1.5     | 84   | 75              | 69  | 63  | 83  | 74  | 68  | 63  | 79  | 73  | 67 | 63 | 77  | 71  | 66 | 62 | 60 |    |
|        |                  | 2.0     | 90   | 82              | 77  | 72  | 88  | 81  | 76  | 71  | 85  | 79  | 75 | 70 | 82  | 77  | 73 | 70 | 67 |    |
| 取付高さ   | 器具間隔最大限          |         | 2.5  | 93              | 87  | 82  | 77  | 92  | 86  | 81  | 77  | 89  | 84 | 80 | 76  | 86  | 82 | 78 | 75 | 72 |
|        | 横方向 (A)          | 縦方向 (B) | 3.0  | 96              | 90  | 86  | 82  | 94  | 89  | 85  | 81  | 91  | 87 | 83 | 80  | 88  | 85 | 82 | 79 | 76 |
| 1.5m   | 1.87m            | 2.13m   | 4.0  | 99              | 94  | 91  | 87  | 97  | 93  | 90  | 87  | 94  | 91 | 88 | 85  | 92  | 89 | 86 | 84 | 81 |
| 2      | 2.47             | 2.68    | 5.0  | 100             | 97  | 94  | 91  | 99  | 96  | 93  | 90  | 96  | 94 | 91 | 89  | 94  | 91 | 89 | 87 | 85 |
| 2.5    | 3.07             | 3.25    | 7.0  | 103             | 100 | 98  | 95  | 101 | 99  | 97  | 95  | 99  | 97 | 95 | 93  | 96  | 94 | 93 | 91 | 89 |
| 3      | 3.67             | 3.84    | 10.0 | 104             | 102 | 101 | 99  | 103 | 101 | 100 | 98  | 100 | 99 | 98 | 96  | 98  | 97 | 96 | 94 | 92 |

