

屋内照明器具特性	
品番 (品名)	LGB16026Z
光源	LDA8L-D-G-E17/S/Z6 ×1 760.0 1 m
管理番号	K0169960(0)DR1
BZ分類	BZ7

器具効率	80%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	32%	床	10%				10%				10%				10%				0%				
下方光束	48%	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	3.8	2.8	2.1	1.7	3.5	2.6	2.0	1.6	3.0	2.3	1.8	1.4	2.5	2.0	1.5	1.2	0.9			
	中	0.63	0.8	4.4	3.4	2.8	2.3	4.1	3.2	2.6	2.2	3.5	2.8	2.3	1.9	3.0	2.4	2.0	1.7	1.2			
	否	0.56	1.0	4.9	3.9	3.3	2.7	4.5	3.7	3.1	2.6	3.9	3.2	2.7	2.3	3.3	2.7	2.3	2.0	1.5			
			1.25	5.3	4.4	3.7	3.2	4.9	4.1	3.5	3.1	4.2	3.6	3.1	2.7	3.6	3.1	2.7	2.4	1.7			
下方投影面積	c m ²	1.5	5.6	4.8	4.1	3.6	5.2	4.5	3.9	3.4	4.5	3.9	3.4	3.0	3.8	3.3	3.0	2.6	2.0				
		2.0	6.0	5.3	4.7	4.2	5.6	5.0	4.5	4.0	4.9	4.3	3.9	3.5	4.1	3.7	3.4	3.1	2.3				
取付高さ	器具間隔最大限		2.5	6.3	5.7	5.2	4.7	5.9	5.3	4.8	4.4	5.1	4.7	4.3	3.9	4.4	4.0	3.7	3.4	2.6			
	横方向 (A)	縦方向 (B)	3.0	6.5	6.0	5.5	5.0	6.1	5.6	5.2	4.8	5.3	4.9	4.5	4.2	4.5	4.2	3.9	3.7	2.8			
H m	1.03 H m	1.03 H m	4.0	6.8	6.3	5.9	5.5	6.4	6.0	5.6	5.2	5.6	5.2	4.9	4.6	4.8	4.5	4.3	4.0	3.1			
			5.0	7.0	6.6	6.2	5.9	6.6	6.2	5.9	5.5	5.7	5.4	5.2	4.9	5.0	4.7	4.5	4.3	3.3			
			7.0	7.2	6.9	6.6	6.3	6.8	6.5	6.2	6.0	5.9	5.7	5.5	5.3	5.2	5.0	4.8	4.6	3.6			
			10.0	7.4	7.1	6.9	6.7	7.0	6.7	6.5	6.3	6.1	5.9	5.8	5.6	5.3	5.2	5.1	4.9	3.9			

