

屋内照明器具特性	
品番 (品名)	LGB80510F
光源	LDA5L-D-G-E17/S/Z4 ×1 440.0 1 m
管理番号	K0139313(0)DR1
BZ分類	BZ4

器具効率	41%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	10%	床	10%				10%				10%				10%				0%			
下方光束	31%	室指数	照明率 (X0.01) ZCM																			
保守率	良	0.67	0.6	23	18	15	13	21	17	14	12	20	16	14	12	18	15	13	11	10		
	中	0.63	0.8	26	22	19	17	25	21	18	16	23	20	17	16	21	18	16	15	13		
	否	0.56	1.0	29	25	22	20	28	24	21	19	25	22	20	18	23	21	19	17	15		
			1.25	31	28	25	23	30	27	24	22	27	25	23	21	25	23	21	20	17		
下方投影面積			1.5	33	30	27	25	32	29	26	24	29	26	25	23	26	24	23	22	19		
			2.0	35	32	30	28	34	31	29	27	31	29	27	26	28	27	25	24	21		
取付高さ	器具間隔最大限		2.5	37	34	32	31	35	33	31	30	32	30	29	28	29	28	27	26	23		
	横方向 (A)	縦方向 (B)	3.0	38	35	34	32	36	34	33	31	33	32	30	29	30	29	28	27	24		
Hm	1.09Hm	1.46Hm	4.0	39	37	36	34	37	36	34	33	34	33	32	31	31	30	30	29	26		
			5.0	39	38	37	36	38	37	36	35	35	34	33	32	32	31	31	30	26		
			7.0	40	39	38	37	39	38	37	36	36	35	34	34	33	32	32	31	28		
			10.0	41	40	39	39	39	39	38	37	36	36	35	35	33	33	33	32	28		

