

屋内照明器具特性	
品番(品名)	LGWJ56009SU
光源	LDA5L-D-G-E17/S/Z4 ×1 440.0 l m
管理番号	K0131555(1)DB1
BZ分類	BZ6

器具効率	35%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	17%	反射率	10%				10%				10%				10%				0%	
下方光束	18%		床	10%				10%				10%				10%				0%
		室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.63	0.6	1.7	1.2	1.0	8	1.5	1.1	9	7	1.3	1.0	8	6	1.0	8	7	5	4
	中	0.6	0.8	2.0	1.6	1.3	1.1	1.8	1.4	1.2	1.0	1.5	1.2	1.0	9	1.2	1.0	9	8	5
	否	0.56	1.0	2.2	1.8	1.5	1.3	2.0	1.7	1.4	1.2	1.7	1.4	1.2	1.1	1.4	1.2	1.0	9	6
			1.25	2.4	2.0	1.8	1.5	2.2	1.9	1.6	1.5	1.8	1.6	1.4	1.3	1.5	1.3	1.2	1.1	8
下方投影面積		cm <sup>2</sup>	1.5	2.5	2.2	1.9	1.7	2.3	2.0	1.8	1.6	1.9	1.7	1.6	1.4	1.6	1.4	1.3	1.2	9
等価発光面積		cm <sup>2</sup>	2.0	2.7	2.4	2.2	2.0	2.5	2.2	2.0	1.9	2.1	1.9	1.8	1.6	1.7	1.6	1.5	1.4	1.0
取付高さ	器具間隔最大限		2.5	2.8	2.6	2.4	2.2	2.6	2.4	2.2	2.1	2.2	2.0	1.9	1.8	1.8	1.7	1.6	1.5	1.1
	横方向(A)	縦方向(B)	3.0	2.9	2.7	2.5	2.3	2.7	2.5	2.3	2.2	2.3	2.1	2.0	1.9	1.9	1.8	1.7	1.6	1.2
Hm	1.47Hm	1.27Hm	4.0	3.0	2.8	2.7	2.5	2.8	2.6	2.5	2.4	2.4	2.3	2.2	2.1	2.0	1.9	1.8	1.3	
			5.0	3.1	2.9	2.8	2.7	2.9	2.7	2.6	2.5	2.4	2.3	2.2	2.2	2.0	2.0	1.9	1.8	1.4
			7.0	3.2	3.0	2.9	2.8	2.9	2.8	2.7	2.7	2.5	2.4	2.4	2.3	2.1	2.1	2.0	2.0	1.4
			10.0	3.2	3.1	3.1	3.0	3.0	2.9	2.9	2.8	2.6	2.5	2.5	2.4	2.2	2.1	2.1	2.0	1.5

