

屋内照明器具特性	
品番(品名)	LGB15041WF
光源	LDA7L-D-G/S/Z6 ×1 810.0 lm
管理番号	K0126485(0)DB1
BZ分類	BZ8

器具効率	91%	反射率	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	38%	床	10%				10%				10%				10%				0%		
下方光束	53%	室指数	照明率 (X0.01)																ZCM		
保守率	良 0.63	0.6	4.2	3.0	2.3	1.8	3.8	2.8	2.2	1.7	3.3	2.4	1.9	1.5	2.7	2.1	1.6	1.2	8		
	中 0.6	0.8	4.9	3.8	3.0	2.5	4.6	3.5	2.8	2.3	3.9	3.0	2.5	2.0	3.2	2.6	2.1	1.7	1.2		
	否 0.56	1.0	5.5	4.4	3.6	3.0	5.0	4.1	3.4	2.8	4.3	3.5	2.9	2.5	3.6	3.0	2.5	2.1	1.5		
		1.25	6.0	5.0	4.2	3.6	5.5	4.6	3.9	3.4	4.7	4.0	3.4	3.0	3.9	3.4	2.9	2.5	1.8		
下方投影面積	cm ²	1.5	6.3	5.4	4.6	4.1	5.9	5.0	4.4	3.8	5.0	4.3	3.8	3.3	4.2	3.7	3.2	2.9	2.1		
等価発光面積		2.0	6.8	6.0	5.3	4.8	6.3	5.6	5.0	4.5	5.4	4.8	4.3	3.9	4.6	4.1	3.7	3.4	2.5		
取付高さ		器具間隔最大限		2.5	7.2	6.4	5.8	5.3	6.7	6.0	5.5	5.0	5.7	5.2	4.7	4.4	4.8	4.4	4.1	3.7	2.8
Hm		1.50Hm	縦方向(B)	3.0	7.4	6.8	6.2	5.7	6.9	6.3	5.8	5.4	5.9	5.5	5.1	4.7	5.0	4.7	4.3	4.0	3.0
		横方向(A)	4.0	7.7	7.2	6.7	6.3	7.2	6.7	6.3	5.9	6.2	5.8	5.5	5.2	5.3	5.0	4.7	4.5	3.4	
			5.0	7.9	7.5	7.0	6.6	7.4	7.0	6.6	6.3	6.4	6.1	5.8	5.5	5.5	5.2	5.0	4.8	3.6	
			7.0	8.2	7.8	7.5	7.1	7.7	7.3	7.0	6.7	6.7	6.4	6.1	5.9	5.7	5.5	5.3	5.1	3.9	
			10.0	8.4	8.1	7.8	7.6	7.9	7.6	7.4	7.1	6.9	6.7	6.5	6.3	5.9	5.8	5.6	5.5	4.2	

