

屋内照明器具特性	
品番 (品名)	LGB15182WF
光源	LDA7L-D-G/S/Z6 x2      810.0 lm
管理番号	K0172592(0)DB1
BZ分類	BZ5

器具効率	43%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	43%	室指数	照明率 ( X0.01)																ZCM	
保守率	良	0.63	0.6	2.4	1.9	1.6	1.3	2.4	1.9	1.6	1.3	2.3	1.8	1.5	1.3	2.2	1.8	1.5	1.3	1.2
	中	0.6	0.8	2.9	2.4	2.0	1.8	2.8	2.3	2.0	1.8	2.7	2.3	2.0	1.8	2.6	2.2	2.0	1.8	1.7
	否	0.56	1.0	3.1	2.7	2.4	2.1	3.1	2.6	2.3	2.1	2.9	2.6	2.3	2.1	2.8	2.5	2.3	2.1	2.0
			1.25	3.4	3.0	2.7	2.4	3.3	2.9	2.7	2.4	3.2	2.9	2.6	2.4	3.1	2.8	2.6	2.4	2.3
下方投影面積		cm <sup>2</sup>	1.5	3.6	3.2	2.9	2.7	3.5	3.2	2.9	2.7	3.4	3.1	2.8	2.6	3.2	3.0	2.8	2.6	2.5
等価発光面積		cm <sup>2</sup>	2.0	3.8	3.5	3.2	3.0	3.7	3.5	3.2	3.0	3.6	3.4	3.2	3.0	3.5	3.3	3.1	3.0	2.8
取付高さ	器具間隔最大限		2.5	4.0	3.7	3.5	3.3	3.9	3.6	3.4	3.3	3.8	3.6	3.4	3.2	3.6	3.5	3.3	3.2	3.1
	横方向 (A)	縦方向 (B)	3.0	4.1	3.8	3.6	3.5	4.0	3.8	3.6	3.4	3.9	3.7	3.5	3.4	3.8	3.6	3.5	3.3	3.2
Hm	1.26Hm	1.26Hm	4.0	4.2	4.0	3.8	3.7	4.1	4.0	3.8	3.7	4.0	3.9	3.7	3.6	3.9	3.8	3.7	3.6	3.5
			5.0	4.3	4.1	4.0	3.9	4.2	4.1	3.9	3.8	4.1	4.0	3.9	3.8	4.0	3.9	3.8	3.7	3.6
			7.0	4.4	4.3	4.1	4.1	4.3	4.2	4.1	4.0	4.2	4.1	4.0	3.9	4.1	4.0	3.9	3.9	3.8
			10.0	4.4	4.4	4.3	4.2	4.4	4.3	4.2	4.2	4.3	4.2	4.1	4.1	4.2	4.1	4.1	4.0	3.9

