

屋内照明器具特性	
品番 (品名)	L G W 5 6 0 0 9 S U
光源	LDA5 L - D - G - E17 / S / Z4 ×1 440.0 l m
管理番号	K0131555 (1) DB1
BZ分類	BZ6

器具効率	35%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	17%	床	10%				10%				10%				10%				0%	
下方光束	18%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.63	0.6	17	12	10	8	15	11	9	7	13	10	8	6	10	8	7	5	4	
	中 0.6	0.8	20	16	13	11	18	14	12	10	15	12	10	9	12	10	9	8	5	
	否 0.56	1.0	22	18	15	13	20	17	14	12	17	14	12	11	14	12	10	9	6	
		1.25	24	20	18	15	22	19	16	15	18	16	14	13	15	13	12	11	8	
下方投影面積	cm ²	1.5	25	22	19	17	23	20	18	16	19	17	16	14	16	14	13	12	9	
		2.0	27	24	22	20	25	22	20	19	21	19	18	16	17	16	15	14	10	
取付高さ	器具間隔最大限		2.5	28	26	24	22	26	24	22	21	22	20	19	18	18	17	16	11	
	横方向 (A)	縦方向 (B)	3.0	29	27	25	23	27	25	23	22	23	21	20	19	19	18	17	12	
Hm	1.47Hm	1.27Hm	4.0	30	28	27	25	28	26	25	24	24	23	22	21	20	19	18	13	
			5.0	31	29	28	27	29	27	26	25	24	23	22	22	20	20	19	14	
			7.0	32	30	29	28	29	28	27	27	25	24	24	23	21	21	20	14	
			10.0	32	31	31	30	30	29	29	28	26	25	25	24	22	21	21	15	

