

# 屋内照明器具特性

品番 (品名)	LGC21104														
光源	LED6200_70_3699 x1 3699.0 lm														
管理番号	K0175412(0)D 1														
BZ分類	BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	8 %																			
下方光束	92 %																			
室指数	照明率 ( X0.01 ) ZCM																			
保守率	良 中 否 0.63 0.6 0.56	0.6	55	43	35	30	53	42	35	29	50	40	34	29	47	39	33	28	26	
		0.8	65	53	45	40	63	52	45	39	59	50	43	38	56	48	42	38	35	
		1.0	71	60	53	47	69	59	52	46	65	57	50	45	61	54	49	44	41	
		1.25	77	67	60	54	75	66	59	53	71	63	57	52	67	60	55	51	47	
下方投影面積	c m <sup>2</sup>	1.5	81	72	65	59	79	71	64	59	74	67	62	57	70	65	60	56	52	
		2.0	87	79	73	68	84	77	72	67	80	74	69	65	76	71	67	63	59	
取付高さ	器具間隔最大限		2.5	90	84	78	73	88	82	77	72	83	78	74	70	79	75	71	68	64
	横方向 (A)	縦方向 (B)	3.0	93	87	82	77	90	85	80	76	86	81	77	74	82	78	75	72	67
H m	1.24 H m	1.24 H m	4.0	96	91	87	83	93	89	85	82	89	85	82	79	85	82	79	77	72
			5.0	98	94	90	87	95	92	89	86	91	88	85	83	87	84	82	80	75
			7.0	100	97	94	92	98	95	92	90	93	91	89	87	89	87	86	84	79
			10.0	102	100	98	96	100	98	96	94	95	94	92	90	91	90	89	87	82

