

屋内照明器具特性	
品番(品名)	LGB19231WF
光源	LDA7L-D-G/S/Z6 ×2 810.0 lm
管理番号	K0126481(0)DB1
BZ分類	BZ8

器具効率	89%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	42%	室指数	床	10%				10%				10%				10%				0%
下方光束	47%		照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	4.0	2.9	2.2	1.7	3.7	2.7	2.0	1.6	3.1	2.3	1.7	1.4	2.5	1.9	1.4	1.1	0.7
	中	0.6	0.8	4.8	3.7	2.9	2.4	4.4	3.4	2.7	2.2	3.6	2.9	2.3	1.9	3.0	2.4	1.9	1.6	1.0
	否	0.56	1.0	5.3	4.2	3.5	2.9	4.9	3.9	3.2	2.7	4.0	3.3	2.7	2.3	3.3	2.7	2.3	1.9	1.3
			1.25	5.8	4.8	4.0	3.5	5.3	4.4	3.8	3.2	4.4	3.7	3.2	2.8	3.6	3.1	2.7	2.3	1.5
下方投影面積		cm ²	1.5	6.1	5.2	4.5	3.9	5.6	4.8	4.2	3.7	4.7	4.1	3.6	3.1	3.9	3.4	3.0	2.6	1.8
等価発光面積		cm ²	2.0	6.6	5.8	5.2	4.6	6.1	5.4	4.8	4.3	5.1	4.6	4.1	3.7	4.2	3.8	3.4	3.1	2.1
取付高さ	器具間隔最大限		2.5	7.0	6.2	5.6	5.1	6.4	5.8	5.2	4.8	5.4	4.9	4.5	4.1	4.5	4.1	3.7	3.4	2.4
	横方向(A)	縦方向(B)	3.0	7.2	6.6	6.0	5.5	6.7	6.1	5.6	5.1	5.6	5.2	4.8	4.4	4.7	4.3	4.0	3.7	2.6
Hm	1.59Hm	1.59Hm	4.0	7.5	7.0	6.5	6.1	7.0	6.5	6.1	5.7	5.9	5.5	5.2	4.9	4.9	4.6	4.4	4.1	2.9
			5.0	7.7	7.2	6.8	6.4	7.2	6.7	6.4	6.0	6.1	5.8	5.5	5.2	5.1	4.8	4.6	4.4	3.2
			7.0	8.0	7.6	7.3	6.9	7.4	7.1	6.8	6.5	6.3	6.1	5.8	5.6	5.3	5.1	4.9	4.8	3.5
			10.0	8.2	7.9	7.6	7.4	7.6	7.3	7.1	6.9	6.5	6.3	6.1	6.0	5.5	5.4	5.2	5.1	3.7

