

屋内照明器具特性	
品番(品名)	LGB19261BF
光源	LDA7L-D-G/S/Z6 ×2 810.0 lm
管理番号	K0126481(0)DB1
BZ分類	BZ8

器具効率	89%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	42%	室指数	床	10%				10%				10%				10%				0%
下方光束	47%		照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	4.0	2.9	2.2	1.7	3.7	2.7	2.0	1.6	3.1	2.3	1.7	1.4	2.5	1.9	1.4	1.1	0.7
	中	0.6	0.8	4.8	3.7	2.9	2.4	4.4	3.4	2.7	2.2	3.6	2.9	2.3	1.9	3.0	2.4	1.9	1.6	1.0
	否	0.56	1.0	5.3	4.2	3.5	2.9	4.9	3.9	3.2	2.7	4.0	3.3	2.7	2.3	3.3	2.7	2.3	1.9	1.3
			1.25	1.5	5.8	4.8	4.0	3.5	5.3	4.4	3.8	3.2	4.4	3.7	3.2	2.8	3.6	3.1	2.7	2.3
下方投影面積		cm ²	2.0	6.6	5.8	5.2	4.6	6.1	5.4	4.8	4.3	5.1	4.6	4.1	3.7	4.2	3.8	3.4	3.1	2.1
等価発光面積		cm ²	2.5	7.0	6.2	5.6	5.1	6.4	5.8	5.2	4.8	5.4	4.9	4.5	4.1	4.5	4.1	3.7	3.4	2.4
	器具間隔最大限		3.0	7.2	6.6	6.0	5.5	6.7	6.1	5.6	5.1	5.6	5.2	4.8	4.4	4.7	4.3	4.0	3.7	2.6
取付高さ	横方向(A)	縦方向(B)	4.0	7.5	7.0	6.5	6.1	7.0	6.5	6.1	5.7	5.9	5.5	5.2	4.9	4.9	4.6	4.4	4.1	2.9
Hm	1.59Hm	1.59Hm	5.0	7.7	7.2	6.8	6.4	7.2	6.7	6.4	6.0	6.1	5.8	5.5	5.2	5.1	4.8	4.6	4.4	3.2
			7.0	8.0	7.6	7.3	6.9	7.4	7.1	6.8	6.5	6.3	6.1	5.8	5.6	5.3	5.1	4.9	4.8	3.5
			10.0	8.2	7.9	7.6	7.4	7.6	7.3	7.1	6.9	6.5	6.3	6.1	6.0	5.5	5.4	5.2	5.1	3.7

