

屋内照明器具特性

品番 (品名)	LGB19341WF														
光源	LDA7L-D-G/S/Z6 ×3 810.0 lm														
管理番号	K0126472(0)DB1														
BZ分類	BZ8														

器具効率	90%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	38%	反射率	10%				10%				10%				10%				0%	
下方光束	52%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)															ZCM		
保守率	良	0.63	0.6	41	30	23	18	38	28	21	17	32	24	18	14	27	20	16	12	8
	中	0.6	0.8	49	38	30	25	45	35	28	23	38	30	24	20	32	25	21	17	12
	否	0.56	1.0	54	43	36	30	50	40	33	28	42	35	29	24	35	29	25	21	14
			1.25	59	49	42	36	55	46	39	34	46	39	34	29	39	33	29	25	18
下方投影面積	cm ²	1.5	63	53	46	40	58	50	43	38	49	43	37	33	41	36	32	28	20	
等価発光面積		2.0	68	60	53	47	63	56	50	45	54	48	43	39	45	40	37	33	24	
取付高さ		器具間隔最大限	2.5	71	64	58	53	66	60	54	49	57	51	47	43	48	44	40	37	27
Hm		横方向 (A)	縦方向 (B)	3.0	74	67	61	57	69	63	58	53	59	54	50	46	50	46	43	40
Hm	1.54Hm	1.55Hm	4.0	77	71	67	62	72	67	62	58	62	58	54	51	52	49	47	44	33
			5.0	79	74	70	66	74	69	66	62	64	60	57	54	54	52	49	47	35
			7.0	81	78	74	71	76	73	70	67	66	63	61	59	57	54	52	51	39
			10.0	83	81	78	75	78	76	73	71	68	66	64	62	58	57	55	54	41

