

屋内照明器具特性

品番 (品名)	LGW80305K	
光源	LED2700_70_348 ×1	348.0 l m
管理番号	K0146953(0)DB1	
BZ分類	BZ6	

器具効率	100%	天井	80%				70%				50%				30%				0%				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	33%	反射率	10%				10%				10%				10%				0%				
下方光束	67%		床	10%				10%				10%				10%				0%			
室指数			照明率 (X0.01)																				ZCM
保守率	良 中 否 0.63 0.6 0.56	0.6	4.9	3.7	2.9	2.3	4.6	3.5	2.7	2.2	4.0	3.1	2.5	2.0	3.5	2.8	2.2	1.9	1.4				
		0.8	5.8	4.6	3.8	3.2	5.4	4.4	3.6	3.1	4.8	3.9	3.3	2.8	4.2	3.5	2.9	2.5	2.0				
		1.0	6.4	5.3	4.5	3.9	6.0	5.0	4.3	3.7	5.3	4.5	3.8	3.4	4.6	4.0	3.4	3.0	2.4				
		1.25	7.0	5.9	5.1	4.5	6.6	5.6	4.9	4.3	5.8	5.0	4.4	3.9	5.0	4.4	4.0	3.6	2.9				
下方投影面積	c m ²	1.5	7.4	6.4	5.6	5.0	6.9	6.1	5.4	4.8	6.1	5.4	4.9	4.4	5.4	4.8	4.3	4.0	3.2				
		2.0	7.9	7.1	6.4	5.8	7.5	6.7	6.1	5.6	6.6	6.0	5.5	5.1	5.8	5.3	4.9	4.6	3.7				
取付高さ	器具間隔最大限		2.5	8.3	7.5	6.9	6.4	7.8	7.2	6.6	6.1	6.9	6.4	5.9	5.5	6.1	5.7	5.3	5.0	4.1			
	横方向 (A)	縦方向 (B)	3.0	8.5	7.9	7.3	6.8	8.1	7.5	7.0	6.5	7.2	6.7	6.3	5.9	6.3	5.9	5.6	5.3	4.4			
H m	1.39 H m	1.39 H m	4.0	8.9	8.3	7.8	7.4	8.4	7.9	7.5	7.1	7.5	7.1	6.7	6.4	6.6	6.3	6.0	5.8	4.7			
			5.0	9.1	8.6	8.2	7.8	8.6	8.2	7.8	7.5	7.7	7.3	7.0	6.8	6.8	6.5	6.3	6.1	5.0			
			7.0	9.3	9.0	8.6	8.3	8.8	8.5	8.2	7.9	7.9	7.7	7.4	7.2	7.0	6.8	6.6	6.5	5.4			
			10.0	9.5	9.3	9.0	8.8	9.0	8.8	8.6	8.3	8.1	7.9	7.7	7.6	7.2	7.1	6.9	6.8	5.6			

