

# 屋内照明器具特性

品番 (品名)	LGB16737														
光源	LLD4000MLCB1 ×1 845.0 lm														
管理番号	K0176239(0)DR1														
BZ分類	BZ5														

器具効率	47%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	2% 45%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.67 0.63 0.56	0.6	2.7	2.1	1.7	1.5	2.6	2.1	1.7	1.5	2.5	2.0	1.7	1.5	2.3	1.9	1.7	1.4	1.3		
		0.8	3.1	2.6	2.2	2.0	3.0	2.5	2.2	1.9	2.9	2.5	2.2	1.9	2.7	2.4	2.1	1.9	1.8		
		1.0	3.4	2.9	2.6	2.3	3.3	2.9	2.5	2.3	3.2	2.8	2.5	2.3	3.0	2.7	2.4	2.2	2.1		
		1.25	3.7	3.2	2.9	2.6	3.6	3.2	2.9	2.6	3.4	3.1	2.8	2.6	3.3	3.0	2.7	2.5	2.4		
下方投影面積 等価発光面積	c m <sup>2</sup> c m <sup>2</sup>	1.5	3.9	3.5	3.2	2.9	3.8	3.4	3.1	2.9	3.6	3.3	3.0	2.8	3.5	3.2	3.0	2.8	2.6		
		2.0	4.1	3.8	3.5	3.3	4.0	3.7	3.5	3.3	3.9	3.6	3.4	3.2	3.7	3.5	3.3	3.1	3.0		
		2.5	4.3	4.0	3.8	3.5	4.2	3.9	3.7	3.5	4.0	3.8	3.6	3.4	3.9	3.7	3.5	3.4	3.2		
取付高さ	器具間隔最大限		3.0	4.4	4.2	3.9	3.7	4.3	4.1	3.9	3.7	4.1	3.9	3.8	3.6	4.0	3.8	3.7	3.5	3.4	
	横方向 (A)	縦方向 (B)																			
H m	0.84 H m	0.84 H m	4.0	4.5	4.3	4.2	4.0	4.5	4.3	4.1	4.0	4.3	4.1	4.0	3.9	4.1	4.0	3.9	3.8	3.6	
			5.0	4.6	4.5	4.3	4.2	4.5	4.4	4.3	4.1	4.4	4.3	4.1	4.0	4.2	4.1	4.0	3.9	3.8	
			7.0	4.7	4.6	4.5	4.4	4.6	4.5	4.4	4.3	4.5	4.4	4.3	4.2	4.3	4.3	4.2	4.1	3.9	
			10.0	4.8	4.7	4.6	4.6	4.7	4.6	4.6	4.5	4.6	4.5	4.4	4.4	4.4	4.4	4.3	4.3	4.1	

