

屋内照明器具特性

品番 (品名)	L G W 8 0 3 0 7 K									
光源	LED2700_70_248 ×1					248.0 l m				
管理番号	K0146941 (0) DB 1									
B Z 分類	B Z 6									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		32 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		68 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																				Z C M
保守率	良	0.63	0.6	4.9	3.7	2.9	2.4	4.6	3.5	2.8	2.3	4.1	3.1	2.5	2.1	3.6	2.8	2.3	1.9	1.5	
	中	0.6	0.8	5.8	4.6	3.8	3.2	5.5	4.4	3.6	3.1	4.8	3.9	3.3	2.8	4.2	3.5	3.0	2.6	2.1	
	否	0.56	1.0	6.4	5.3	4.5	3.9	6.0	5.0	4.3	3.7	5.3	4.5	3.9	3.4	4.7	4.0	3.5	3.1	2.5	
			1.25	7.0	5.9	5.2	4.5	6.6	5.6	4.9	4.4	5.8	5.0	4.5	4.0	5.1	4.5	4.0	3.6	2.9	
下方投影面積	c m ²		1.5	7.4	6.4	5.7	5.1	7.0	6.1	5.4	4.9	6.2	5.5	4.9	4.4	5.4	4.9	4.4	4.0	3.3	
	等価発光面積		c m ²	2.0	7.9	7.1	6.4	5.9	7.5	6.7	6.1	5.6	6.6	6.0	5.5	5.1	5.9	5.4	5.0	4.6	3.8
取付高さ	器具間隔最大限		2.5	8.3	7.6	6.9	6.4	7.8	7.2	6.6	6.1	7.0	6.4	6.0	5.6	6.1	5.7	5.4	5.0	4.1	
	横方向 (A)	縦方向 (B)	3.0	8.6	7.9	7.3	6.8	8.1	7.5	7.0	6.5	7.2	6.7	6.3	5.9	6.4	6.0	5.7	5.4	4.4	
H m	1.37 H m	1.37 H m	4.0	8.9	8.3	7.9	7.4	8.4	7.9	7.5	7.1	7.5	7.1	6.8	6.4	6.7	6.3	6.1	5.8	4.8	
			5.0	9.1	8.6	8.2	7.8	8.6	8.2	7.8	7.5	7.7	7.4	7.1	6.8	6.9	6.6	6.3	6.1	5.1	
			7.0	9.3	9.0	8.6	8.3	8.9	8.5	8.2	7.9	8.0	7.7	7.4	7.2	7.1	6.9	6.7	6.5	5.4	
			10.0	9.5	9.3	9.0	8.8	9.1	8.8	8.6	8.4	8.2	8.0	7.8	7.6	7.3	7.1	7.0	6.8	5.7	

