

# 屋内照明器具特性

品番 (品名)	LGB16738				
光源	LLD4000LCB1 ×1                      845.0 lm				
管理番号	K0176246(0)DR1				
BZ分類	BZ5/0.7/BZ4/2.3/BZ5				

器具効率	46%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	2%	室指数	照明率 ( X0.01 )																ZCM		
下方光束	44%																				
保守率	良 0.67 中 0.63 否 0.56	0.6	26	21	17	15	25	20	17	15	24	20	17	15	23	19	17	15	14		
		0.8	31	25	22	19	30	25	22	19	28	24	21	19	27	24	21	19	18		
		1.0	33	29	25	23	33	28	25	23	31	27	25	22	30	27	24	22	21		
		1.25	36	32	29	26	35	31	28	26	34	30	28	26	32	29	27	25	24		
下方投影面積 等価発光面積	c m <sup>2</sup>	1.5	38	34	31	29	37	33	31	28	35	32	30	28	34	31	29	27	26		
		2.0	40	37	34	32	40	37	34	32	38	35	33	31	36	34	32	31	29		
		2.5	42	39	37	35	41	39	36	34	39	37	35	34	38	36	35	33	32		
取付高さ	器具間隔最大限		3.0	43	41	38	37	42	40	38	36	41	39	37	36	39	37	36	35	33	
	横方向 (A)	縦方向 (B)																			
H m	0.85 H m	0.85 H m	4.0	44	42	41	39	44	42	40	39	42	41	39	38	41	39	38	37	36	
			5.0	45	44	42	41	44	43	42	40	43	42	41	39	41	40	39	39	37	
			7.0	46	45	44	43	45	44	43	42	44	43	42	41	42	42	41	40	39	
			10.0	47	46	45	44	46	45	45	44	45	44	43	43	43	43	42	42	40	

