

屋内照明器具特性

品番 (品名) **LGB16738**

光源 **LLD3020LCE1 ×1** **795.0 lm**

管理番号 **K0176251(0)DR1**

BZ分類 **BZ1**

器具効率	65%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	65%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	54	50	47	45	53	49	47	45	52	49	47	45	52	48	46	45	44	
	中 0.63	0.8	58	54	51	49	57	53	51	49	56	53	51	49	55	52	50	49	48	
	否 0.56	1.0	60	57	54	52	59	56	54	52	58	55	53	52	57	55	53	52	51	
下方投影面積	cm ²	1.25	62	59	57	55	61	59	56	55	60	58	56	54	59	57	55	54	53	
		1.5	63	61	59	57	63	60	58	57	61	59	58	56	60	58	57	56	55	
等価発光面積	cm ²	2.0	65	63	61	60	64	62	61	59	63	61	60	59	62	60	59	58	57	
		2.5	66	64	63	61	66	64	62	61	64	63	61	60	63	62	61	60	58	
取付高さ	器具間隔最大限		3.0	67	65	64	63	66	65	63	62	65	64	62	62	64	63	62	61	59
	横方向 (A)	縦方向 (B)	4.0	68	67	65	64	67	66	65	64	66	65	64	63	64	64	63	62	61
Hm	0.46Hm	0.46Hm	5.0	68	67	66	66	68	67	66	65	66	65	65	64	65	64	64	63	62
			7.0	69	68	68	67	68	68	67	66	67	66	66	65	66	65	65	64	63
			10.0	70	69	68	68	69	68	68	67	67	67	67	66	66	65	65	63	63

