

屋内照明器具特性

品番 (品名) **LGB16738**

光源 **LLD3020LCB1 x1** **795.0 lm**

管理番号 **K0176252(0)DR1**

BZ分類 **BZ1**

器具効率	60%	天井	80%				70%				50%				30%				0%
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	
上方光束	0%	反射率	10%				10%				10%				10%				0%
下方光束	60%		室指数	照明率 (X 0.01)															
保守率	良 0.67	0.6	50	46	43	42	49	45	43	41	48	45	43	41	48	45	43	41	41
	中 0.63	0.8	53	50	47	45	53	49	47	45	52	49	47	45	51	48	46	45	44
	否 0.56	1.0	55	52	50	48	55	52	50	48	54	51	49	48	53	51	49	48	47
下方投影面積	cm ²	1.25	57	54	52	51	57	54	52	50	55	53	52	50	54	53	51	50	49
		1.5	58	56	54	52	58	56	54	52	57	55	53	52	56	54	53	51	50
等価発光面積	cm ²	2.0	60	58	56	55	59	58	56	55	58	57	55	54	57	56	55	54	53
		2.5	61	59	58	57	60	59	57	56	59	58	57	56	58	57	56	55	54
取付高さ	器具間隔最大限		3.0	62	60	59	58	61	60	59	57	60	59	58	57	59	58	57	56
	横方向 (A)	縦方向 (B)	4.0	63	61	60	59	62	61	60	59	61	60	59	58	59	59	58	57
Hm	0.46Hm	0.46Hm	5.0	63	62	61	60	62	62	61	60	61	60	60	59	60	59	59	58
			7.0	64	63	62	62	63	62	62	61	62	61	61	60	60	60	60	59
			10.0	64	64	63	63	63	63	62	62	62	61	61	61	61	60	60	58

