

屋内照明器具特性

品番 (品名)	LGB16738	
光源	LLD2000LCE1 ×1	531.0 lm
管理番号	K0176250(0)DR1	
BZ分類	BZ5/0.7/BZ4/2.3/BZ5	

器具効率	60%	天井	80%				70%				50%				30%				0%				
	上方光束		2%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
	下方光束		58%		床	10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																				ZCM		
保守率	良 中 否	0.67	0.6	3.5	2.8	2.3	2.0	3.4	2.7	2.3	2.0	3.2	2.6	2.2	2.0	3.1	2.6	2.2	1.9	1.8			
		0.63	0.8	4.1	3.4	2.9	2.6	4.0	3.3	2.9	2.6	3.8	3.2	2.8	2.5	3.6	3.1	2.8	2.5	2.4			
		0.56	1.0	4.4	3.8	3.4	3.0	4.3	3.8	3.3	3.0	4.1	3.6	3.3	3.0	4.0	3.5	3.2	2.9	2.8			
			1.25	4.8	4.2	3.8	3.5	4.7	4.2	3.8	3.4	4.5	4.0	3.7	3.4	4.3	3.9	3.6	3.3	3.2			
下方投影面積	等価発光面積	cm ²	1.5	5.0	4.5	4.1	3.8	4.9	4.4	4.1	3.8	4.7	4.3	4.0	3.7	4.5	4.2	3.9	3.6	3.5			
			2.0	5.4	4.9	4.6	4.3	5.2	4.8	4.5	4.2	5.0	4.7	4.4	4.2	4.8	4.5	4.3	4.1	3.9			
			2.5	5.6	5.2	4.9	4.6	5.4	5.1	4.8	4.6	5.2	4.9	4.7	4.5	5.0	4.8	4.6	4.4	4.2			
取付高さ	器具間隔最大限		Hm	0.85Hm	0.85Hm	3.0	5.7	5.4	5.1	4.9	5.6	5.3	5.0	4.8	5.4	5.1	4.9	4.7	5.2	5.0	4.8	4.6	4.4
	4.0	5.9				5.6	5.4	5.2	5.8	5.5	5.3	5.1	5.6	5.4	5.2	5.0	5.4	5.2	5.1	4.9	4.7		
			5.0	6.0	5.8	5.6	5.4	5.9	5.7	5.5	5.4	5.7	5.5	5.4	5.2	5.5	5.4	5.2	5.1	4.9			
			7.0	6.1	6.0	5.8	5.7	6.0	5.9	5.7	5.6	5.8	5.7	5.6	5.5	5.6	5.5	5.4	5.3	5.1			
			10.0	6.2	6.1	6.0	5.9	6.1	6.0	5.9	5.8	5.9	5.8	5.8	5.7	5.7	5.7	5.6	5.5	5.3			

