

屋内照明器具特性

品番 (品名) **LGB16738**

光源 **LLD3020MLCB1 ×1** **715.0 lm**

管理番号 **K0176255(0)DR1**

BZ分類 **BZ1**

器具効率	59%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	59%		室指数	照明率 (X0.01)																ZCM
保守率	良 0.67	0.6	49	45	43	41	48	45	42	41	48	44	42	41	47	44	42	41	40	
	中 0.63	0.8	52	49	46	45	52	49	46	45	51	48	46	45	50	48	46	44	44	
	否 0.56	1.0	54	51	49	47	54	51	49	47	53	50	49	47	52	50	48	47	46	
下方投影面積	cm ²	1.25	56	54	51	50	56	53	51	50	55	52	51	49	54	52	50	49	48	
		1.5	58	55	53	52	57	55	53	51	56	54	52	51	55	53	52	51	50	
等価発光面積	cm ²	2.0	59	57	55	54	59	57	55	54	57	56	54	53	56	55	54	53	52	
		2.5	60	58	57	56	60	58	57	55	58	57	56	55	57	56	55	54	53	
取付高さ	器具間隔最大限		3.0	61	59	58	57	60	59	58	57	59	58	57	56	58	57	56	55	54
	横方向 (A)	縦方向 (B)	4.0	62	60	59	59	61	60	59	58	60	59	58	57	59	58	57	56	55
Hm	0.46Hm	0.46Hm	5.0	62	61	60	60	62	61	60	59	60	59	59	58	59	58	58	57	56
			7.0	63	62	61	61	62	61	61	60	61	60	60	59	60	59	59	58	57
			10.0	63	63	62	62	63	62	62	61	61	61	60	60	60	59	59	58	57

