

# 屋内照明器具特性

品番 (品名) **LGB16738**

光源 **LLD2020MLCE1 ×1** **460.0lm**

管理番号 **K0176256(0)DR1**

BZ分類 **BZ1**

| 器具効率   | 79%             | 天井      | 80%         |     |    |    | 70% |     |    |    | 50% |     |    |    | 30% |     |    |    | 0%  |    |
|--------|-----------------|---------|-------------|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|----|
|        |                 |         | 70          | 50  | 30 | 10 | 70  | 50  | 30 | 10 | 70  | 50  | 30 | 10 | 70  | 50  | 30 | 10 |     |    |
| 上方光束   | 0%              | 反射率     | 壁           | 10% |    |    |     | 10% |    |    |     | 10% |    |    |     | 10% |    |    |     | 0% |
| 下方光束   | 79%             |         | 床           | 10% |    |    |     | 10% |    |    |     | 10% |    |    |     | 10% |    |    |     | 0% |
|        |                 | 室指数     | 照明率 (X0.01) |     |    |    |     |     |    |    |     |     |    |    |     |     |    |    | ZCM |    |
| 保守率    | 良 0.67          | 0.6     | 65          | 60  | 57 | 55 | 65  | 60  | 57 | 55 | 64  | 59  | 57 | 55 | 63  | 59  | 56 | 54 | 54  |    |
|        | 中 0.63          | 0.8     | 70          | 65  | 62 | 60 | 69  | 65  | 62 | 60 | 68  | 64  | 62 | 60 | 67  | 64  | 61 | 59 | 58  |    |
|        | 否 0.56          | 1.0     | 73          | 69  | 66 | 63 | 72  | 68  | 65 | 63 | 71  | 67  | 65 | 63 | 69  | 67  | 64 | 63 | 62  |    |
| 下方投影面積 | cm <sup>2</sup> | 1.25    | 75          | 72  | 69 | 67 | 75  | 71  | 68 | 66 | 73  | 70  | 68 | 66 | 72  | 69  | 67 | 66 | 64  |    |
|        |                 | 1.5     | 77          | 74  | 71 | 69 | 76  | 73  | 71 | 69 | 75  | 72  | 70 | 68 | 73  | 71  | 69 | 68 | 66  |    |
| 等価発光面積 | cm <sup>2</sup> | 2.0     | 79          | 76  | 74 | 72 | 78  | 76  | 74 | 72 | 77  | 75  | 73 | 71 | 75  | 73  | 72 | 71 | 69  |    |
|        |                 | 2.5     | 80          | 78  | 76 | 74 | 80  | 77  | 76 | 74 | 78  | 76  | 75 | 73 | 76  | 75  | 74 | 72 | 71  |    |
| 取付高さ   | 器具間隔最大限         |         | 3.0         | 81  | 79 | 78 | 76  | 80  | 79 | 77 | 76  | 79  | 77 | 76 | 75  | 77  | 76 | 75 | 74  | 72 |
|        | 横方向 (A)         | 縦方向 (B) | 4.0         | 82  | 81 | 79 | 78  | 82  | 80 | 79 | 78  | 80  | 79 | 78 | 77  | 78  | 77 | 76 | 76  | 74 |
| Hm     | 0.46Hm          | 0.46Hm  | 5.0         | 83  | 82 | 81 | 80  | 82  | 81 | 80 | 79  | 81  | 80 | 79 | 78  | 79  | 78 | 77 | 75  |    |
|        |                 |         | 7.0         | 84  | 83 | 82 | 81  | 83  | 82 | 81 | 81  | 81  | 81 | 80 | 79  | 80  | 79 | 78 | 76  |    |
|        |                 |         | 10.0        | 84  | 84 | 83 | 83  | 84  | 83 | 82 | 82  | 82  | 81 | 81 | 80  | 80  | 79 | 79 | 77  |    |

