

# 屋内照明器具特性

品番 (品名)	L G W C 8 0 3 3 7 K				
光源	LED5000_70_225 x1 225.0 l m				
管理番号	K0160249 ( 0 ) DR 1				
B Z 分類	B Z 9				

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																	
		床	10 %				10 %				10 %				10 %				0 %																	
上方光束	50 %	室指数																	照明率 ( X 0 . 0 1 )																	Z C M
下方光束	50 %																																			
保守率	良 中 否	0.63	0.6	0.56																																
		0.6	0.6	0.56	0.6	45	32	24	19	41	30	22	17	33	25	19	14	27	20	15	11	6														
		0.6	0.6	0.56	0.8	53	41	32	26	48	37	30	24	39	31	25	20	32	25	20	16	10														
		0.56	0.6	0.56	1.0	59	47	38	32	53	43	35	29	44	36	30	25	35	29	24	20	12														
下方投影面積	c m <sup>2</sup>	1.25																																		
		1.5	64	53	45	38	59	49	41	35	48	40	34	30	39	33	28	24	15																	
		2.0	68	58	50	43	62	53	46	40	51	44	38	34	41	36	31	27	17																	
等価発光面積	c m <sup>2</sup>	2.5	74	65	57	51	68	59	53	47	56	50	44	40	45	40	36	33	21																	
		3.0	77	69	62	56	71	64	58	52	59	53	49	44	48	44	40	37	24																	
取付高さ	器具間隔最大限																																			
	横方向 ( A )	縦方向 ( B )																																		
H m	1.07 H m		1.52 H m																																	
	1.07 H m		1.52 H m		4.0	80	73	66	61	74	67	61	57	61	56	52	48	50	46	43	40	27														
	1.07 H m		1.52 H m		5.0	83	77	72	67	77	72	67	62	65	60	57	53	53	50	47	44	30														
	1.07 H m		1.52 H m		7.0	86	81	76	71	79	75	70	66	67	63	60	57	55	52	49	47	32														
	1.07 H m		1.52 H m		10.0	88	84	81	77	82	78	75	72	69	66	64	61	57	55	53	51	36														
	1.07 H m		1.52 H m		10.0	91	88	85	82	84	81	79	76	71	69	67	65	59	58	56	54	39														

