

屋内照明器具特性

品番 (品名)	L G W 4 6 1 4 7 K														
光源	LED2700_70_17 x1 17.0 l m														
管理番号	K0130420(0)DB1														
BZ分類	BZ5/0.7/BZ4														

器具効率	100%	天井	80%				70%				50%				30%				0%				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	0%	反射率	10%				10%				10%				10%				0%				
下方光束	100%		床	10%				10%				10%				10%				0%			
		室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	58	46	38	33	56	45	38	33	54	44	37	32	52	43	37	32	30			
	中	0.6	0.8	68	57	49	43	66	56	49	43	64	55	48	43	61	53	47	43	41			
	否	0.56	1.0	75	64	57	51	73	63	56	51	70	62	56	51	68	60	55	50	48			
			1.25	81	71	64	59	79	70	64	59	76	69	63	58	73	67	62	58	55			
下方投影面積			1.5	85	76	70	64	83	75	69	64	80	73	68	64	77	72	67	63	61			
	等価発光面積		2.0	90	83	78	73	89	82	77	72	86	80	76	72	83	78	74	71	69			
取付高さ	器具間隔最大限		2.5	94	88	83	79	92	87	82	78	89	85	81	77	87	83	79	76	74			
	横方向 (A)	縦方向 (B)	3.0	96	91	87	83	95	90	86	82	92	88	84	81	89	86	83	80	78			
1.5m	1.88m	1.88m	4.0	99	95	92	88	98	94	91	88	95	92	89	87	92	90	87	85	83			
2	2.54	2.51	5.0	101	98	95	92	100	97	94	91	97	94	92	90	94	92	90	88	86			
2.5	3.18	3.14	7.0	103	101	98	96	102	100	97	96	99	97	96	94	97	95	94	92	90			
3	3.82	3.77	10.0	105	103	101	100	103	102	100	99	101	100	98	97	99	97	96	95	92			

