

屋内照明器具特性

品番 (品名)	L G W 8 5 0 1 1 U														
光源	LDA5 L - D - G - E17 / S / Z4 ×1 440.0 1 m														
管理番号	K0175936 (0) DR 1														
B Z 分類	B Z 6														

器具効率	79 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		40 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		39 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01) ZCM																				
保守率	良	0.63	0.6	37	28	22	18	34	26	21	17	29	22	18	15	24	19	15	13	8	
	中	0.6	0.8	44	35	29	25	41	33	27	23	34	28	23	20	28	23	20	17	12	
	否	0.56	1.0	49	40	34	30	45	37	32	28	38	32	28	24	31	27	23	21	14	
	下方投影面積	c m ²		1.25	53	45	40	35	49	42	37	33	41	36	32	28	34	30	27	24	17
等価発光面積	c m ²		1.5	56	49	43	39	52	46	41	37	44	39	35	32	36	32	29	27	19	
	c m ²		2.0	61	54	49	45	56	50	46	42	47	43	39	36	39	36	33	31	22	
取付高さ	器具間隔最大限		2.5	63	58	53	49	58	54	50	46	49	46	43	40	41	38	36	34	24	
	横方向 (A)	縦方向 (B)	3.0	65	60	56	53	60	56	52	49	51	48	45	43	42	40	38	36	26	
1.5m	2.13 m	1.95 m	4.0	68	64	60	57	63	59	56	53	53	51	48	46	44	42	41	39	28	
2	2.85	2.57	5.0	69	66	63	60	64	61	59	56	55	52	50	49	46	44	42	41	30	
2.5	3.54	3.2	7.0	71	69	66	64	66	64	62	60	56	55	53	52	47	46	45	44	32	
3	4.25	3.84	10.0	73	71	69	67	67	66	64	63	58	56	55	54	48	48	47	46	33	

