

屋内照明器具特性	
品番 (品名)	LGW85280Z
光源	LDA5L-D-G-E17/S/Z4 ×1 440.0 l m
管理番号	K0175939(0)DR1
BZ分類	BZ8/0.7/BZ7

器具効率	81%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	38%	室指数	床	10%				10%				10%				10%				0%
下方光束	43%		照明率 (X0.01) ZCM																	
保守率	良	0.63	0.6	3.7	2.7	2.1	1.6	3.4	2.5	1.9	1.5	2.8	2.1	1.7	1.3	2.3	1.8	1.4	1.1	7
	中	0.6	0.8	4.4	3.4	2.8	2.3	4.0	3.2	2.6	2.1	3.4	2.7	2.2	1.8	2.8	2.2	1.8	1.5	10
	否	0.56	1.0	4.9	4.0	3.3	2.8	4.5	3.7	3.1	2.6	3.8	3.1	2.6	2.2	3.1	2.6	2.2	1.9	13
			1.25	5.3	4.5	3.8	3.3	4.9	4.1	3.6	3.1	4.1	3.5	3.0	2.7	3.4	2.9	2.6	2.3	16
下方投影面積		cm ²	1.5	5.7	4.9	4.2	3.7	5.2	4.5	3.9	3.5	4.4	3.8	3.4	3.0	3.6	3.2	2.8	2.5	18
等価発光面積		cm ²	2.0	6.1	5.4	4.8	4.4	5.6	5.0	4.5	4.1	4.8	4.3	3.9	3.5	3.9	3.6	3.3	3.0	21
取付高さ	器具間隔最大限		2.5	6.4	5.8	5.3	4.8	5.9	5.4	4.9	4.5	5.0	4.6	4.2	3.9	4.2	3.8	3.6	3.3	24
	横方向 (A)	縦方向 (B)	3.0	6.6	6.1	5.6	5.2	6.1	5.6	5.2	4.8	5.2	4.8	4.5	4.2	4.3	4.0	3.8	3.6	26
H _m	1.51H _m	1.73H _m	4.0	6.9	6.4	6.0	5.7	6.4	6.0	5.6	5.3	5.5	5.1	4.9	4.6	4.6	4.3	4.1	3.9	28
			5.0	7.1	6.7	6.3	6.0	6.6	6.2	5.9	5.6	5.6	5.3	5.1	4.9	4.7	4.5	4.3	4.1	30
			7.0	7.3	7.0	6.7	6.4	6.8	6.5	6.3	6.0	5.8	5.6	5.4	5.2	4.9	4.7	4.6	4.4	33
			10.0	7.4	7.2	7.0	6.8	6.9	6.7	6.6	6.4	6.0	5.8	5.7	5.5	5.1	4.9	4.8	4.7	35

