

屋内照明器具特性	
品番 (品名)	LGW85281YZ
光源	LDA5L-D-G-E17/S/Z4 ×1 440.0 l m
管理番号	K0175940(0)DR1
BZ分類	BZ7/0.9/BZ6

器具効率	70%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	32%	反射率	10%				10%				10%				10%				0%	
下方光束	38%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.63	0.6	3.3	2.4	1.9	1.5	3.0	2.2	1.7	1.4	2.5	1.9	1.5	1.2	2.1	1.6	1.3	1.0	7	
	中 0.6	0.8	3.9	3.0	2.5	2.1	3.6	2.8	2.3	1.9	3.0	2.4	2.0	1.7	2.5	2.0	1.7	1.5	1.0	
	否 0.56	1.0	4.3	3.5	2.9	2.5	4.0	3.3	2.7	2.4	3.3	2.8	2.4	2.1	2.8	2.4	2.0	1.8	1.3	
下方投影面積	cm ²	1.25	4.7	3.9	3.4	3.0	4.3	3.7	3.2	2.8	3.7	3.1	2.8	2.4	3.0	2.7	2.3	2.1	1.5	
		1.5	5.0	4.3	3.8	3.3	4.6	4.0	3.5	3.1	3.9	3.4	3.0	2.7	3.2	2.9	2.6	2.3	1.7	
等価発光面積	cm ²	2.0	5.3	4.8	4.3	3.9	5.0	4.4	4.0	3.7	4.2	3.8	3.5	3.2	3.5	3.2	3.0	2.7	2.0	
		2.5	5.6	5.1	4.6	4.3	5.2	4.7	4.4	4.0	4.4	4.1	3.8	3.5	3.7	3.5	3.2	3.0	2.2	
取付高さ	器具間隔最大限		3.0	5.8	5.3	4.9	4.6	5.4	5.0	4.6	4.3	4.6	4.3	4.0	3.8	3.9	3.6	3.4	3.2	2.4
	横方向 (A)	縦方向 (B)	4.0	6.0	5.6	5.3	5.0	5.6	5.3	5.0	4.7	4.8	4.5	4.3	4.1	4.1	3.9	3.7	3.5	2.6
Hm	1.28Hm	1.73Hm	5.0	6.1	5.8	5.5	5.3	5.7	5.4	5.2	5.0	4.9	4.7	4.5	4.3	4.2	4.0	3.9	3.7	2.8
			7.0	6.3	6.1	5.8	5.6	5.9	5.7	5.5	5.3	5.1	4.9	4.8	4.6	4.3	4.2	4.1	4.0	3.0
			10.0	6.5	6.3	6.1	5.9	6.0	5.9	5.7	5.6	5.2	5.1	5.0	4.9	4.5	4.4	4.3	4.2	3.2

