

屋内照明器具特性	
品番 (品名)	L G W C 8 5 0 1 2 U
光源	LDA5 L - D - G - E17 / S / Z4 ×1 440.0 l m
管理番号	K0188013 (0) DB 1
B Z 分類	B Z 7

器具効率	62 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	36 %	室指数																		
下方光束	26 %	照明率 (X0.01)																		
		Z C M																		
保守率	良 中 否	0.63	0.6	2.8	2.1	1.6	1.3	2.6	1.9	1.5	1.2	2.1	1.6	1.2	1.0	1.6	1.2	1.0	0.8	0.4
		0.6	0.8	3.3	2.6	2.1	1.8	3.0	2.4	2.0	1.6	2.4	2.0	1.6	1.4	1.9	1.6	1.3	1.1	0.6
		0.56	1.0	3.7	3.0	2.5	2.2	3.4	2.8	2.3	2.0	2.7	2.3	1.9	1.7	2.1	1.8	1.5	1.3	0.8
			1.25	4.0	3.4	2.9	2.6	3.7	3.1	2.7	2.4	3.0	2.6	2.2	2.0	2.3	2.0	1.8	1.6	1.0
下方投影面積		c m ²																		
等価発光面積		c m ²																		
取付高さ	器具間隔最大限		2.5	4.8	4.4	4.0	3.7	4.4	4.0	3.7	3.4	3.6	3.3	3.1	2.9	2.9	2.7	2.5	2.3	1.5
	横方向 (A)	縦方向 (B)	3.0	5.0	4.6	4.3	4.0	4.6	4.2	3.9	3.7	3.7	3.5	3.3	3.1	3.0	2.8	2.6	2.5	1.6
1.5m	2.6m	2m	4.0	5.2	4.9	4.6	4.3	4.8	4.5	4.2	4.0	3.9	3.7	3.5	3.3	3.1	3.0	2.8	2.7	1.7
2	3.46	2.65	5.0	5.3	5.0	4.8	4.6	4.9	4.6	4.4	4.2	4.0	3.8	3.7	3.5	3.2	3.1	3.0	2.9	1.9
2.5	4.3	3.28	7.0	5.5	5.3	5.1	4.9	5.0	4.8	4.7	4.5	4.2	4.0	3.9	3.8	3.4	3.3	3.2	3.1	2.0
3	5.16	3.94	10.0	5.6	5.4	5.3	5.1	5.1	5.0	4.9	4.7	4.3	4.2	4.1	4.0	3.5	3.4	3.3	3.2	2.1

