

屋内照明器具特性	
品番 (品名)	LGWC47001
光源	LLD2000MLCB1 ×1 531.0 lm
管理番号	K0176342(0)DR1
BZ分類	BZ3/0.9/BZ2/4.5/BZ3/6.0/BZ2

器具効率	62%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	0%	床	10%				10%				10%				10%				0%			
下方光束	62%	室指数	照明率 (X0.01) ZCM																			
保守率	良 0.63	0.6	4.0	3.4	3.0	2.7	3.9	3.3	2.9	2.7	3.8	3.3	2.9	2.7	3.7	3.2	2.9	2.7	2.5			
	中 0.6	0.8	4.7	4.1	3.7	3.4	4.6	4.0	3.7	3.4	4.4	4.0	3.6	3.4	4.3	3.9	3.6	3.4	3.2			
	否 0.56	1.0	5.1	4.5	4.2	3.9	5.0	4.5	4.1	3.9	4.8	4.4	4.1	3.9	4.7	4.3	4.1	3.8	3.7			
		1.25	5.4	4.9	4.6	4.3	5.3	4.9	4.6	4.3	5.2	4.8	4.5	4.3	5.0	4.7	4.5	4.3	4.1			
下方投影面積	cm ²	1.5	5.6	5.2	4.9	4.6	5.5	5.1	4.9	4.6	5.4	5.0	4.8	4.6	5.2	5.0	4.7	4.5	4.4			
		2.0	5.9	5.6	5.3	5.1	5.8	5.5	5.3	5.0	5.6	5.4	5.2	5.0	5.5	5.3	5.1	4.9	4.8			
取付高さ	器具間隔最大限		2.5	6.1	5.8	5.5	5.3	6.0	5.7	5.5	5.3	5.8	5.6	5.4	5.3	5.7	5.5	5.3	5.2	5.1		
	横方向 (A)	縦方向 (B)	3.0	6.2	5.9	5.7	5.5	6.1	5.9	5.7	5.5	5.9	5.7	5.6	5.4	5.8	5.6	5.5	5.4	5.2		
Hm	1.17Hm	1.17Hm	4.0	6.3	6.1	6.0	5.8	6.2	6.1	5.9	5.8	6.1	5.9	5.8	5.7	5.9	5.8	5.7	5.6	5.5		
			5.0	6.4	6.2	6.1	6.0	6.3	6.2	6.0	5.9	6.2	6.0	5.9	5.8	6.0	5.9	5.8	5.8	5.6		
			7.0	6.5	6.4	6.3	6.2	6.4	6.3	6.2	6.1	6.3	6.2	6.1	6.0	6.1	6.0	6.0	5.9	5.8		
			10.0	6.6	6.5	6.4	6.3	6.5	6.4	6.3	6.3	6.3	6.3	6.2	6.2	6.2	6.1	6.1	6.0	5.9		

