

屋内照明器具特性

品番 (品名)	LSLD900K	
光源	LLD2020LSCE1 ×1	460.0 lm
管理番号	K0175531(0)DR1	
BZ分類	BZ1	

器具効率	96%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	96%	床	10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	79	73	69	67	79	73	69	67	77	72	69	67	76	72	69	66	65
	中	0.63	0.8	85	80	76	73	84	79	76	73	83	78	75	73	81	78	75	73	72
	否	0.56	1.0	89	84	80	78	88	83	80	78	86	82	79	77	85	81	79	77	76
下方投影面積	等価発光面積	cm ²	1.25	92	87	84	82	91	87	84	82	89	86	83	81	87	85	82	81	79
			1.5	94	90	87	85	93	89	87	84	91	88	86	84	89	87	85	83	82
取付高さ	器具間隔最大限		2.5	98	95	93	91	97	94	92	91	95	93	91	90	93	91	90	89	87
	横方向 (A)	縦方向 (B)	3.0	99	96	95	93	98	96	94	92	96	94	93	91	94	92	91	90	88
Hm	0.41Hm	0.41Hm	4.0	100	98	97	95	99	97	96	95	97	96	94	93	95	94	93	92	90
			5.0	101	99	98	97	100	98	97	96	98	96	96	95	96	95	94	93	91
			7.0	102	100	99	99	100	99	99	98	98	98	97	96	96	96	95	95	92
			10.0	102	101	101	100	101	100	100	99	99	98	98	97	97	96	96	96	93

