

# 屋内照明器具特性

|         |                 |          |
|---------|-----------------|----------|
| 品番 (品名) | LGWC47001       |          |
| 光源      | LLD3020MLCB1 ×1 | 715.0 lm |
| 管理番号    | K0176347(0)DR1  |          |
| BZ分類    | BZ1             |          |

|        |                 |         |                 |        |     |        |     |     |     |     |     |     |    |    |     |     |    |    |    |     |    |    |    |    |
|--------|-----------------|---------|-----------------|--------|-----|--------|-----|-----|-----|-----|-----|-----|----|----|-----|-----|----|----|----|-----|----|----|----|----|
| 器具効率   | 96%             | 天井      | 80%             |        |     |        | 70% |     |     |     | 50% |     |    |    | 30% |     |    |    | 0% |     |    |    |    |    |
|        | 上方光束<br>0%      |         | 壁               | 70     | 50  | 30     | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10 | 0%  |    |    |    |    |
| 下方光束   | 96%             | 床       |                 | 10%    |     |        |     | 10% |     |     |     | 10% |    |    |     | 10% |    |    |    | 0%  |    |    |    |    |
| 室指数    | 照明率 (X0.01)     |         |                 |        |     |        |     |     |     |     |     |     |    |    |     |     |    |    |    | ZCM |    |    |    |    |
| 保守率    | 良 0.63          | 0.6     | 0.6             | 82     | 76  | 73     | 70  | 81  | 76  | 72  | 70  | 80  | 75 | 72 | 70  | 79  | 75 | 72 | 70 | 69  |    |    |    |    |
|        | 中 0.6           |         | 0.8             | 87     | 82  | 79     | 77  | 87  | 82  | 79  | 76  | 85  | 81 | 78 | 76  | 84  | 80 | 78 | 76 | 75  |    |    |    |    |
|        | 否 0.56          |         | 1.0             | 91     | 86  | 83     | 81  | 90  | 86  | 83  | 81  | 88  | 85 | 82 | 80  | 87  | 84 | 82 | 80 | 79  |    |    |    |    |
| 下方投影面積 | cm <sup>2</sup> | 等価発光面積  | cm <sup>2</sup> | 1.25   | 94  | 90     | 87  | 84  | 93  | 89  | 86  | 84  | 91 | 88 | 86  | 84  | 90 | 87 | 85 | 83  | 82 |    |    |    |
|        |                 |         |                 | 1.5    | 95  | 92     | 89  | 87  | 95  | 91  | 89  | 87  | 93 | 90 | 88  | 86  | 91 | 89 | 87 | 86  | 84 |    |    |    |
| 取付高さ   | 器具間隔最大限         |         | Hm              | 0.41Hm | Hm  | 0.41Hm | 2.5 | 99  | 97  | 95  | 93  | 98  | 96 | 94 | 93  | 96  | 94 | 93 | 92 | 94  | 93 | 92 | 91 | 89 |
|        | 横方向 (A)         | 縦方向 (B) |                 |        |     |        | 3.0 | 100 | 98  | 96  | 95  | 99  | 97 | 96 | 94  | 97  | 96 | 94 | 93 | 95  | 94 | 93 | 92 | 90 |
| Hm     | 0.41Hm          | 0.41Hm  | 4.0             | 101    | 100 | 98     | 97  | 100 | 99  | 97  | 96  | 98  | 97 | 96 | 95  | 96  | 95 | 94 | 94 | 91  |    |    |    |    |
|        |                 |         | 5.0             | 102    | 101 | 99     | 98  | 101 | 100 | 98  | 97  | 99  | 98 | 97 | 96  | 97  | 96 | 95 | 95 | 92  |    |    |    |    |
| Hm     | 0.41Hm          | 0.41Hm  | 7.0             | 103    | 102 | 101    | 100 | 102 | 101 | 100 | 99  | 99  | 99 | 98 | 97  | 97  | 97 | 96 | 96 | 93  |    |    |    |    |
|        |                 |         | 10.0            | 103    | 102 | 102    | 101 | 102 | 101 | 101 | 100 | 100 | 99 | 99 | 98  | 98  | 98 | 97 | 97 | 94  |    |    |    |    |

