

# 屋内照明器具特性

品番 (品名)	L G W 8 0 3 3 5 K														
光源	LED5000_70_329 x1 329.0 l m														
管理番号	K0146950(0)DB1														
BZ分類	BZ6														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %			
上方光束	28 %	室指数	照明率 ( X0.01)															ZCM		
下方光束	72 %																			
保守率	良 中 否 0.63 0.6 0.56	0.6	4.9	3.7	2.8	2.3	4.6	3.5	2.7	2.2	4.1	3.2	2.5	2.0	3.6	2.8	2.3	1.9	1.5	
		0.8	5.8	4.6	3.7	3.1	5.5	4.4	3.6	3.0	4.9	3.9	3.3	2.8	4.3	3.6	3.0	2.6	2.1	
		1.0	6.4	5.2	4.4	3.8	6.1	5.0	4.2	3.6	5.4	4.5	3.9	3.4	4.8	4.1	3.5	3.1	2.5	
		1.25	7.0	5.9	5.1	4.4	6.6	5.6	4.9	4.3	5.9	5.1	4.4	3.9	5.2	4.6	4.0	3.6	3.0	
下方投影面積	c m <sup>2</sup>	1.5	7.4	6.4	5.6	5.0	7.0	6.1	5.3	4.8	6.2	5.5	4.9	4.4	5.5	4.9	4.4	4.0	3.3	
		2.0	7.9	7.1	6.3	5.7	7.5	6.7	6.1	5.5	6.7	6.1	5.5	5.1	6.0	5.5	5.0	4.6	3.9	
取付高さ	器具間隔最大限		2.5	8.3	7.5	6.9	6.3	7.9	7.2	6.6	6.0	7.0	6.5	6.0	5.6	6.3	5.8	5.4	4.3	
	横方向 (A)	縦方向 (B)	3.0	8.5	7.8	7.2	6.7	8.1	7.5	6.9	6.5	7.3	6.8	6.3	5.9	6.5	6.1	5.7	4.6	
H m	1.40 H m	1.40 H m	4.0	8.9	8.3	7.8	7.3	8.5	7.9	7.5	7.0	7.6	7.2	6.8	6.5	6.8	6.5	6.2	5.0	
			5.0	9.1	8.6	8.2	7.7	8.7	8.2	7.8	7.4	7.8	7.5	7.1	6.8	7.0	6.8	6.5	5.3	
			7.0	9.4	9.0	8.6	8.3	8.9	8.6	8.3	7.9	8.1	7.8	7.5	7.3	7.3	7.1	6.9	5.7	
			10.0	9.6	9.3	9.0	8.7	9.2	8.9	8.6	8.4	8.3	8.1	7.9	7.7	7.5	7.4	7.2	6.0	

