

# 屋内照明器具特性

品番 (品名)	L G W C 8 1 3 3 5 K																
光源	LED5000_70_330 x1 330.0 l m																
管理番号	K0149624 ( 0 ) DR 1																
B Z 分類	BZ9 / 0.9 / BZ8 / 1.1 / BZ9																

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束	50 % 50 %	室指数	照明率 ( X0.01 ) ZCM																		
保守率	良 中 否 0.63 0.6 0.56	0.6	45	32	24	19	41	30	22	17	33	25	19	14	27	20	15	12	6		
		0.8	53	41	32	26	48	37	30	24	40	31	25	20	32	25	20	16	10		
		1.0	59	47	38	32	54	43	35	30	44	36	30	25	35	29	24	20	12		
		1.25	64	53	45	38	59	49	41	35	48	41	35	30	39	33	28	24	15		
下方投影面積 等価発光面積	c m <sup>2</sup> c m <sup>2</sup>	1.5	68	58	50	43	62	53	46	40	51	44	38	34	41	36	31	28	17		
		2.0	74	65	57	51	68	60	53	47	56	50	44	40	45	41	36	33	21		
		2.5	77	69	62	57	71	64	58	53	59	54	49	45	48	44	40	37	24		
取付 高さ	器具間隔最大限		3.0	80	73	67	61	74	67	62	57	61	56	52	48	50	46	43	27		
	横方向 ( A ) H m	縦方向 ( B ) H m	4.0	84	77	72	67	77	72	67	63	65	60	57	53	53	50	47	30		
			5.0	86	81	76	72	79	75	70	67	67	63	60	57	55	52	50	33		
			7.0	89	84	81	77	82	78	75	72	69	66	64	61	57	55	53	36		
			10.0	91	88	85	82	84	81	79	76	72	69	67	65	60	58	56	39		

