

| 屋内照明器具特性 |   |
|----------|---|
| 品番 (品名)  | LGWC47007                                     |
| 光源       | LLD4000LCB1 ×1                      845.0 l m |
| 管理番号     | K0176339 ( 0 ) DR 1                           |
| B Z 分類   | BZ3 / 0.9 / BZ2 / 4.5 / BZ3 / 6.0 / BZ2       |

|        |                 |         |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |      |     |     |     |
|--------|-----------------|---------|------|----|----|------|------|----|----|------|------|----|----|------|------|----|----|------|-----|-----|-----|
| 器具効率   | 64 %            | 天井      | 80 % |    |    |      | 70 % |    |    |      | 50 % |    |    |      | 30 % |    |    |      | 0 % |     |     |
|        | 上方光束            |         | 0 %  | 壁  | 70 | 50   | 30   | 10 | 70 | 50   | 30   | 10 | 70 | 50   | 30   | 10 | 70 | 50   | 30  | 10  | 0 % |
|        | 下方光束            |         | 64 % |    | 床  | 10 % |      |    |    | 10 % |      |    |    | 10 % |      |    |    | 10 % |     |     |     |
| 室指数    | 照明率 ( X0.01 )   |         |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |      |     | ZCM |     |
| 保守率    | 良               | 0.63    | 0.6  | 41 | 35 | 30   | 27   | 41 | 34 | 30   | 27   | 39 | 34 | 30   | 27   | 38 | 33 | 30   | 27  | 26  |     |
|        | 中               | 0.6     | 0.8  | 48 | 42 | 38   | 35   | 47 | 42 | 38   | 35   | 46 | 41 | 37   | 35   | 44 | 40 | 37   | 35  | 33  |     |
|        | 否               | 0.56    | 1.0  | 52 | 47 | 43   | 40   | 51 | 46 | 43   | 40   | 50 | 45 | 42   | 40   | 48 | 45 | 42   | 39  | 38  |     |
|        |                 |         | 1.25 | 55 | 51 | 47   | 45   | 55 | 50 | 47   | 44   | 53 | 49 | 46   | 44   | 52 | 48 | 46   | 44  | 43  |     |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5  | 58 | 54 | 50   | 48   | 57 | 53 | 50   | 47   | 55 | 52 | 49   | 47   | 54 | 51 | 49   | 47  | 45  |     |
| 等価発光面積 | cm <sup>2</sup> |         | 2.0  | 61 | 57 | 54   | 52   | 60 | 57 | 54   | 52   | 58 | 55 | 53   | 51   | 57 | 54 | 52   | 51  | 49  |     |
| 取付高さ   | 器具間隔最大限         |         | 2.5  | 62 | 59 | 57   | 55   | 61 | 59 | 57   | 55   | 60 | 58 | 56   | 54   | 58 | 56 | 55   | 53  | 52  |     |
|        | 横方向 (A)         | 縦方向 (B) | 3.0  | 63 | 61 | 59   | 57   | 63 | 60 | 58   | 57   | 61 | 59 | 57   | 56   | 60 | 58 | 57   | 55  | 54  |     |
| Hm     | 1.17Hm          | 1.17Hm  | 4.0  | 65 | 63 | 61   | 60   | 64 | 62 | 61   | 59   | 62 | 61 | 60   | 58   | 61 | 60 | 59   | 58  | 56  |     |
|        |                 |         | 5.0  | 66 | 64 | 63   | 61   | 65 | 63 | 62   | 61   | 63 | 62 | 61   | 60   | 62 | 61 | 60   | 59  | 58  |     |
|        |                 |         | 7.0  | 67 | 66 | 64   | 64   | 66 | 65 | 64   | 63   | 64 | 63 | 63   | 62   | 63 | 62 | 62   | 61  | 59  |     |
|        |                 |         | 10.0 | 67 | 67 | 66   | 65   | 67 | 66 | 65   | 64   | 65 | 65 | 64   | 63   | 64 | 63 | 63   | 62  | 60  |     |

