

屋内照明器具特性

品番 (品名)	LGWC47022	
光源	LLD3020MLCB1 ×1	715.0 lm
管理番号	K0176347(0)DR1	
BZ分類	BZ1	

器具効率	96%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	96%	床	10%				10%				10%				10%				0%	
室指数		照明率 (X0.01)	ZCM																	
保守率	良 0.63	0.6	0.6	82	76	73	70	81	76	72	70	80	75	72	70	79	75	72	70	69
	中 0.6	0.56	0.8	87	82	79	77	87	82	79	76	85	81	78	76	84	80	78	76	75
	否 0.56	1.0	91	86	83	81	90	86	83	81	88	85	82	80	87	84	82	80	79	
下方投影面積	cm ²	1.25	94	90	87	84	93	89	86	84	91	88	86	84	90	87	85	83	82	
		1.5	95	92	89	87	95	91	89	87	93	90	88	86	91	89	87	86	84	
等価発光面積	cm ²	2.0	98	95	93	91	97	94	92	90	95	93	91	89	93	91	90	89	87	
		2.5	99	97	95	93	98	96	94	93	96	94	93	92	94	93	92	91	89	
取付高さ	器具間隔最大限		3.0	100	98	96	95	99	97	96	94	97	96	94	93	95	94	93	92	90
	横方向 (A)	縦方向 (B)	4.0	101	100	98	97	100	99	97	96	98	97	96	95	96	95	94	94	91
Hm	0.41Hm	0.41Hm	5.0	102	101	99	98	101	100	98	97	99	98	97	96	97	96	95	95	92
			7.0	103	102	101	100	102	101	100	99	99	99	98	97	97	97	96	96	93
			10.0	103	102	102	101	102	101	101	100	100	99	99	98	98	98	97	94	

