

屋内照明器具特性	
品番 (品名)	LGB15125BZ
光源	LDA7L-D-G/S/Z6 ×1 810.0 lm
管理番号	K0155055(0)DB1
BZ分類	BZ8

器具効率	84%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	35%	床	10%				10%				10%				10%				0%	
下方光束	49%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.63	0.6	3.8	2.7	2.1	1.6	3.5	2.5	1.9	1.5	3.0	2.2	1.7	1.3	2.5	1.8	1.4	1.1	7	
	中 0.6	0.8	4.5	3.5	2.7	2.2	4.2	3.2	2.6	2.1	3.5	2.8	2.2	1.8	2.9	2.3	1.9	1.6	1.1	
	否 0.56	1.0	5.0	4.0	3.3	2.7	4.6	3.7	3.1	2.6	3.9	3.2	2.7	2.2	3.3	2.7	2.3	1.9	1.3	
		1.25	5.5	4.5	3.8	3.3	5.1	4.2	3.6	3.1	4.3	3.6	3.1	2.7	3.6	3.1	2.6	2.3	1.6	
下方投影面積	cm ²	1.5	5.8	4.9	4.2	3.7	5.4	4.6	4.0	3.5	4.6	4.0	3.5	3.0	3.8	3.3	2.9	2.6	1.9	
等価発光面積		2.0	6.3	5.5	4.9	4.4	5.8	5.2	4.6	4.1	5.0	4.4	4.0	3.6	4.2	3.8	3.4	3.1	2.3	
取付高さ		器具間隔最大限		2.5	6.6	5.9	5.3	4.9	6.1	5.5	5.0	4.6	5.3	4.8	4.4	4.0	4.4	4.1	3.7	2.5
H _m		1.84H _m	縦方向 (B)	3.0	6.8	6.2	5.7	5.2	6.4	5.8	5.3	4.9	5.5	5.0	4.7	4.3	4.6	4.3	4.0	2.8
		横方向 (A)	4.0	7.1	6.6	6.2	5.8	6.7	6.2	5.8	5.4	5.8	5.4	5.1	4.8	4.9	4.6	4.4	3.1	
			5.0	7.3	6.9	6.5	6.1	6.8	6.5	6.1	5.8	5.9	5.6	5.3	5.1	5.1	4.8	4.6	3.3	
			7.0	7.6	7.2	6.9	6.6	7.1	6.8	6.5	6.2	6.2	5.9	5.7	5.5	5.3	5.1	4.9	3.6	
			10.0	7.7	7.5	7.2	7.0	7.3	7.0	6.8	6.6	6.4	6.2	6.0	5.8	5.5	5.3	5.2	3.9	

