

屋内照明器具特性	
品番 (品名)	L G W 8 5 0 5 5 W F
光源	L D A 5 L - D - G - E 1 7 / S / Z 4 × 1      4 4 0 . 0 l m
管理番号	K 0 1 7 5 9 2 8 ( 0 ) D R 1
B Z 分類	B Z 1 0 / 0 . 7 / B Z 9

器具効率	41 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	20 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	21 %		室指数	照明率 ( X 0 . 0 1 )																Z C M
保守率	良	0.63	0.6	1.8	1.2	0.9	0.7	1.6	1.1	0.8	0.6	1.3	0.9	0.7	1.0	0.7	0.5	0.4	0.2	
	中	0.6	0.8	2.1	1.6	1.2	1.0	1.9	1.4	1.1	0.9	1.5	1.2	0.9	0.7	1.2	1.0	0.7	0.3	
	否	0.56	1.0	2.3	1.8	1.5	1.2	2.1	1.7	1.3	1.1	1.7	1.4	1.1	0.9	1.4	1.1	0.9	0.4	
			1.25	2.5	2.1	1.7	1.4	2.3	1.9	1.6	1.3	1.9	1.6	1.3	1.1	1.5	1.3	1.1	0.5	
下方投影面積		cm <sup>2</sup>	1.5	2.7	2.3	1.9	1.7	2.5	2.1	1.8	1.5	2.0	1.7	1.5	1.3	1.6	1.4	1.2	0.6	
等価発光面積		cm <sup>2</sup>	2.0	2.9	2.6	2.2	2.0	2.7	2.3	2.1	1.8	2.2	2.0	1.7	1.5	1.8	1.6	1.4	0.8	
取付高さ	器具間隔最大限		2.5	3.1	2.7	2.5	2.2	2.8	2.5	2.3	2.0	2.4	2.1	1.9	1.7	1.9	1.7	1.6	0.9	
	横方向 (A)	縦方向 (B)	3.0	3.2	2.9	2.6	2.4	2.9	2.7	2.4	2.2	2.5	2.2	2.0	1.9	2.0	1.8	1.7	1.0	
H <sub>m</sub>	1.39 H <sub>m</sub>	2.25 H <sub>m</sub>	4.0	3.3	3.1	2.9	2.7	3.1	2.9	2.6	2.5	2.6	2.4	2.2	2.1	2.1	2.0	1.9	1.2	
			5.0	3.4	3.2	3.0	2.8	3.2	3.0	2.8	2.6	2.7	2.5	2.4	2.2	2.2	2.1	2.0	1.3	
			7.0	3.6	3.4	3.2	3.1	3.3	3.1	3.0	2.9	2.8	2.7	2.5	2.4	2.3	2.2	2.1	1.4	
			10.0	3.7	3.5	3.4	3.3	3.4	3.3	3.2	3.0	2.9	2.8	2.7	2.6	2.4	2.3	2.3	1.6	

