

屋内照明器具特性	
品番 (品名)	S F 2 9 1 W F
光源	LDA7L - D - G / S / Z 6 × 1                      8 1 0 . 0 1 m
管理番号	K 0 1 2 7 2 8 5 ( 1 ) D B 1
B Z 分類	B Z 9

器具効率	9 0 %	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
			壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
上方光束	4 7 %	床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
下方光束	4 3 %		1 0 %				1 0 %				1 0 %				1 0 %				0 %	
		室指数	照明率 ( X 0 . 0 1 )																Z C M	
保守率	良	0 . 6 3	0 . 6	3 9	2 8	2 1	1 6	3 6	2 6	1 9	1 5	2 9	2 1	1 6	1 2	2 3	1 7	1 3	9	5
	中	0 . 6	0 . 8	4 7	3 6	2 8	2 3	4 2	3 3	2 6	2 1	3 4	2 7	2 1	1 7	2 7	2 1	1 7	1 4	7
	否	0 . 5 6	1 . 0	5 2	4 1	3 4	2 8	4 7	3 8	3 1	2 6	3 8	3 1	2 5	2 1	3 0	2 5	2 0	1 7	9
			1 . 2 5	5 7	4 7	3 9	3 3	5 2	4 3	3 6	3 1	4 2	3 5	3 0	2 5	3 3	2 8	2 4	2 0	1 2
下方投影面積		c m <sup>2</sup>	1 . 5	6 0	5 1	4 4	3 8	5 5	4 7	4 0	3 5	4 5	3 9	3 3	2 9	3 6	3 1	2 7	2 3	1 4
等価発光面積			c m <sup>2</sup>	2 . 0	6 5	5 7	5 0	4 5	6 0	5 2	4 6	4 1	4 9	4 3	3 9	3 5	3 9	3 5	3 1	2 8
取付高さ	器具間隔最大限		2 . 5	6 9	6 1	5 5	5 0	6 3	5 6	5 1	4 6	5 2	4 7	4 3	3 9	4 2	3 8	3 4	3 1	2 0
	横方向 ( A )	縦方向 ( B )	3 . 0	7 1	6 5	5 9	5 4	6 5	5 9	5 4	5 0	5 4	4 9	4 5	4 2	4 3	4 0	3 7	3 4	2 2
H m	0 . 0 0 H m	0 . 0 0 H m	4 . 0	7 4	6 9	6 4	6 0	6 8	6 3	5 9	5 5	5 7	5 3	5 0	4 6	4 6	4 3	4 0	3 8	2 5
			5 . 0	7 6	7 2	6 7	6 3	7 0	6 6	6 2	5 9	5 9	5 5	5 2	5 0	4 8	4 5	4 3	4 1	2 7
			7 . 0	7 9	7 5	7 2	6 8	7 3	6 9	6 6	6 3	6 1	5 8	5 6	5 4	5 0	4 8	4 6	4 4	3 0
			1 0 . 0	8 1	7 8	7 5	7 3	7 5	7 2	7 0	6 7	6 3	6 1	5 9	5 7	5 2	5 0	4 9	4 7	3 3

