

|          |                                 |
|----------|---------------------------------|
| 屋内照明器具特性 |                                 |
| 品番(品名)   | LGB15061WF                      |
| 光源       | LDA7L-D-G/S/Z6 ×1      810.0 lm |
| 管理番号     | K0126485(0)DB1                  |
| BZ分類     | BZ8                             |

|         |                 |        |               |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|---------|-----------------|--------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率    | 91%             | 反射率    | 天井            | 80% |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|         |                 |        | 壁             | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |     |
| 上方光束    | 38%             | 床      | 10%           |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |     |     |
| 下方光束    | 53%             | 室指数    | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |     |     |
| 保守率     | 良 0.63          | 0.6    | 4.2           | 3.0 | 2.3 | 1.8 | 3.8 | 2.8 | 2.2 | 1.7 | 3.3 | 2.4 | 1.9 | 1.5 | 2.7 | 2.1 | 1.6 | 1.2 | 8   |     |     |
|         | 中 0.6           | 0.8    | 4.9           | 3.8 | 3.0 | 2.5 | 4.6 | 3.5 | 2.8 | 2.3 | 3.9 | 3.0 | 2.5 | 2.0 | 3.2 | 2.6 | 2.1 | 1.7 | 1.2 |     |     |
|         | 否 0.56          | 1.0    | 5.5           | 4.4 | 3.6 | 3.0 | 5.0 | 4.1 | 3.4 | 2.8 | 4.3 | 3.5 | 2.9 | 2.5 | 3.6 | 3.0 | 2.5 | 2.1 | 1.5 |     |     |
|         |                 | 1.25   | 6.0           | 5.0 | 4.2 | 3.6 | 5.5 | 4.6 | 3.9 | 3.4 | 4.7 | 4.0 | 3.4 | 3.0 | 3.9 | 3.4 | 2.9 | 2.5 | 1.8 |     |     |
| 下方投影面積  | cm <sup>2</sup> | 1.5    | 6.3           | 5.4 | 4.6 | 4.1 | 5.9 | 5.0 | 4.4 | 3.8 | 5.0 | 4.3 | 3.8 | 3.3 | 4.2 | 3.7 | 3.2 | 2.9 | 2.1 |     |     |
|         |                 | 2.0    | 6.8           | 6.0 | 5.3 | 4.8 | 6.3 | 5.6 | 5.0 | 4.5 | 5.4 | 4.8 | 4.3 | 3.9 | 4.6 | 4.1 | 3.7 | 3.4 | 2.5 |     |     |
| 等価発光面積  | cm <sup>2</sup> | 2.5    | 7.2           | 6.4 | 5.8 | 5.3 | 6.7 | 6.0 | 5.5 | 5.0 | 5.7 | 5.2 | 4.7 | 4.4 | 4.8 | 4.4 | 4.1 | 3.7 | 2.8 |     |     |
|         |                 | 3.0    | 7.4           | 6.8 | 6.2 | 5.7 | 6.9 | 6.3 | 5.8 | 5.4 | 5.9 | 5.5 | 5.1 | 4.7 | 5.0 | 4.7 | 4.3 | 4.0 | 3.0 |     |     |
| 取付高さ Hm | 器具間隔最大限         | 1.50Hm | 1.50Hm        | 4.0 | 7.7 | 7.2 | 6.7 | 6.3 | 7.2 | 6.7 | 6.3 | 5.9 | 6.2 | 5.8 | 5.5 | 5.2 | 5.3 | 5.0 | 4.7 | 4.5 | 3.4 |
|         | 横方向(A)          | 縦方向(B) | 5.0           | 7.9 | 7.5 | 7.0 | 6.6 | 7.4 | 7.0 | 6.6 | 6.3 | 6.4 | 6.1 | 5.8 | 5.5 | 5.5 | 5.2 | 5.0 | 4.8 | 4.8 | 3.6 |
|         |                 |        | 7.0           | 8.2 | 7.8 | 7.5 | 7.1 | 7.7 | 7.3 | 7.0 | 6.7 | 6.7 | 6.4 | 6.1 | 5.9 | 5.7 | 5.5 | 5.3 | 5.1 | 5.1 | 3.9 |
|         |                 |        | 10.0          | 8.4 | 8.1 | 7.8 | 7.6 | 7.9 | 7.6 | 7.4 | 7.1 | 6.9 | 6.7 | 6.5 | 6.3 | 5.9 | 5.8 | 5.6 | 5.5 | 5.5 | 4.2 |

