

# 屋内照明器具特性

品番 (品名)	LGWC47100	
光源	LLD2020LCB1 ×1	460.0 l m
管理番号	K0176348 ( 0 ) DR 1	
BZ分類	BZ1	

器具効率	91 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	91 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 ( X0.01 )																			ZCM
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
下方投影面積	等価発光面積	cm <sup>2</sup>	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	89	90	92	94	95	96	96	97	98
		cm <sup>2</sup>	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	89	90	92	94	95	96	96	97	98	98
取付高さ	器具間隔最大限		2.5	3.0	4.0	5.0	7.0	10.0	89	90	92	94	95	96	96	97	98	98	98	98
H m	横方向 (A)	縦方向 (B)	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41
	H m	H m	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41	0.41

