

屋内照明器具特性

品番 (品名)	LGB57518K				
光源	LDA7L-D-G/S/Z6	x5	810.0 lm		
管理番号	K0165408(0)DB1				
BZ分類	BZ6				

器具効率	88%	天井	80%				70%				50%				30%				0%		
	上方光束		25%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		63%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	4.4	3.4	2.7	2.2	4.2	3.2	2.6	2.1	3.7	2.9	2.4	2.0	3.3	2.7	2.2	1.8	1.5	
	中	0.63	0.8	5.2	4.2	3.5	3.0	4.9	4.0	3.3	2.9	4.4	3.6	3.1	2.7	3.9	3.3	2.8	2.5	2.1	
	否	0.56	1.0	5.8	4.8	4.1	3.5	5.4	4.6	3.9	3.4	4.9	4.1	3.6	3.2	4.3	3.7	3.3	2.9	2.5	
			1.25	6.2	5.3	4.7	4.1	5.9	5.1	4.5	4.0	5.3	4.6	4.1	3.7	4.7	4.2	3.8	3.4	2.9	
下方投影面積	c m ²		1.5	6.6	5.8	5.1	4.6	6.3	5.5	4.9	4.4	5.6	5.0	4.5	4.1	5.0	4.5	4.1	3.8	3.2	
	等価発光面積		c m ²	2.0	7.1	6.4	5.8	5.3	6.7	6.1	5.5	5.1	6.0	5.5	5.1	4.7	5.4	5.0	4.6	4.3	3.7
取付高さ	器具間隔最大限		2.5	7.4	6.8	6.2	5.8	7.0	6.5	6.0	5.6	6.3	5.9	5.5	5.1	5.7	5.3	5.0	4.7	4.0	
	横方向 (A)	縦方向 (B)	3.0	7.6	7.1	6.6	6.2	7.2	6.7	6.3	5.9	6.5	6.1	5.8	5.5	5.9	5.6	5.3	5.0	4.3	
H m	1.14 H m	1.14 H m	4.0	7.9	7.4	7.0	6.7	7.5	7.1	6.8	6.4	6.8	6.5	6.2	5.9	6.2	5.9	5.6	5.4	4.6	
			5.0	8.1	7.7	7.3	7.0	7.7	7.4	7.0	6.8	7.0	6.7	6.5	6.2	6.3	6.1	5.9	5.7	4.9	
			7.0	8.3	8.0	7.7	7.5	7.9	7.7	7.4	7.2	7.2	7.0	6.8	6.6	6.5	6.4	6.2	6.0	5.2	
			10.0	8.5	8.2	8.0	7.8	8.1	7.9	7.7	7.5	7.4	7.2	7.1	6.9	6.7	6.6	6.5	6.3	5.5	

