

屋内照明器具特性

品番 (品名)	LGB57565K				
光源	LDA7L-D-G/S/Z6	x5	810.0 lm		
管理番号	K0164952(0)DB1				
BZ分類	BZ6				

器具効率	89%	天井	80%				70%				50%				30%				0%		
	上方光束		26%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		63%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	4.4	3.2	2.5	2.0	4.1	3.1	2.4	2.0	3.6	2.8	2.2	1.8	3.2	2.5	2.0	1.7	1.3	
	中	0.63	0.8	5.1	4.0	3.3	2.8	4.8	3.9	3.2	2.7	4.3	3.5	2.9	2.5	3.8	3.1	2.6	2.3	1.8	
	否	0.56	1.0	5.7	4.6	3.9	3.3	5.3	4.4	3.7	3.2	4.7	4.0	3.4	2.9	4.2	3.6	3.1	2.7	2.2	
			1.25	6.2	5.2	4.5	3.9	5.8	4.9	4.3	3.8	5.2	4.5	3.9	3.5	4.6	4.0	3.5	3.2	2.6	
下方投影面積	cm ²		1.5	6.5	5.6	4.9	4.4	6.2	5.4	4.7	4.2	5.5	4.8	4.3	3.9	4.9	4.3	3.9	3.5	2.9	
等価発光面積	cm ²		2.0	7.0	6.2	5.6	5.1	6.6	5.9	5.4	4.9	5.9	5.4	4.9	4.5	5.3	4.8	4.4	4.1	3.4	
取付高さ	器具間隔最大限		2.5	7.4	6.7	6.1	5.6	7.0	6.3	5.8	5.4	6.2	5.7	5.3	4.9	5.6	5.2	4.8	4.5	3.8	
	横方向 (A)	縦方向 (B)	3.0	7.6	7.0	6.5	6.0	7.2	6.6	6.2	5.8	6.5	6.0	5.6	5.3	5.8	5.4	5.1	4.8	4.1	
Hm	1.12Hm	1.12Hm	4.0	7.9	7.4	6.9	6.5	7.5	7.1	6.6	6.3	6.8	6.4	6.1	5.8	6.1	5.8	5.5	5.3	4.4	
			5.0	8.1	7.7	7.3	6.9	7.7	7.3	7.0	6.6	7.0	6.6	6.4	6.1	6.2	6.0	5.8	5.6	4.7	
			7.0	8.3	8.0	7.7	7.4	7.9	7.6	7.4	7.1	7.2	6.9	6.7	6.5	6.5	6.3	6.1	5.9	5.1	
			10.0	8.5	8.3	8.0	7.8	8.1	7.9	7.7	7.5	7.4	7.2	7.0	6.9	6.7	6.5	6.4	6.3	5.3	

