

屋内照明器具特性	
品番 (品名)	LGB19680K
光源	LDA7L-D-G/S/Z6 x6 810.0 lm
管理番号	K0164950(0)DB1
BZ分類	BZ6

器具効率	88%	天井	80%				70%				50%				30%				0%		
	上方光束		31%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	57%	床	10%				10%				10%				10%				0%		
室指数		照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	4.4	3.4	2.7	2.2	4.1	3.2	2.6	2.1	3.6	2.9	2.3	2.0	3.2	2.6	2.1	1.8	1.4	
	中	0.63	0.8	5.2	4.2	3.5	2.9	4.9	3.9	3.3	2.8	4.3	3.5	3.0	2.6	3.7	3.1	2.7	2.3	1.9	
	否	0.56	1.0	5.7	4.7	4.0	3.5	5.3	4.5	3.8	3.3	4.7	4.0	3.5	3.0	4.1	3.5	3.1	2.8	2.2	
			1.25	6.2	5.3	4.6	4.1	5.8	5.0	4.4	3.9	5.1	4.4	3.9	3.5	4.4	3.9	3.5	3.2	2.6	
下方投影面積		cm ²	1.5	6.5	5.7	5.0	4.5	6.1	5.4	4.8	4.3	5.4	4.8	4.3	3.9	4.7	4.2	3.8	3.5	2.8	
等価発光面積		cm ²	2.0	7.0	6.3	5.7	5.2	6.6	5.9	5.4	4.9	5.8	5.3	4.8	4.5	5.1	4.7	4.3	4.0	3.3	
取付高さ	器具間隔最大限		2.5	7.3	6.6	6.1	5.7	6.9	6.3	5.8	5.4	6.1	5.6	5.2	4.9	5.3	5.0	4.6	4.4	3.6	
	横方向 (A)	縦方向 (B)	3.0	7.5	6.9	6.4	6.0	7.1	6.6	6.1	5.7	6.3	5.9	5.5	5.2	5.5	5.2	4.9	4.6	3.8	
Hm	1.38Hm	1.37Hm	4.0	7.8	7.3	6.9	6.5	7.4	6.9	6.6	6.2	6.5	6.2	5.9	5.6	5.8	5.5	5.3	5.0	4.1	
			5.0	8.0	7.6	7.2	6.9	7.5	7.2	6.9	6.6	6.7	6.4	6.2	5.9	5.9	5.7	5.5	5.3	4.3	
			7.0	8.2	7.9	7.6	7.3	7.8	7.5	7.2	7.0	6.9	6.7	6.5	6.3	6.1	6.0	5.8	5.6	4.6	
			10.0	8.4	8.1	7.9	7.7	7.9	7.7	7.5	7.3	7.1	6.9	6.8	6.6	6.3	6.2	6.0	5.9	4.9	

