

屋内照明器具特性	
品番 (品名)	L G W C 4 7 1 0 7
光源	LLD2000MLCB1 ×1 531.0 lm
管理番号	K0176342 (0) DR 1
B Z 分類	BZ3 / 0.9 / BZ2 / 4.5 / BZ3 / 6.0 / BZ2

器具効率	62 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	62 %	室指数	照明率 (X 0.01)																Z C M	
保守率	良 0.63 中 0.6 否 0.56	0.6	40	34	30	27	39	33	29	27	38	33	29	27	37	32	29	27	25	
		0.8	47	41	37	34	46	40	37	34	44	40	36	34	43	39	36	34	32	
		1.0	51	45	42	39	50	45	41	39	48	44	41	39	47	43	41	38	37	
		1.25	54	49	46	43	53	49	46	43	52	48	45	43	50	47	45	43	41	
下方投影面積	c m ²	1.5	56	52	49	46	55	51	49	46	54	50	48	46	52	50	47	45	44	
		2.0	59	56	53	51	58	55	53	50	56	54	52	50	55	53	51	49	48	
取付高さ	器具間隔最大限		2.5	61	58	55	53	60	57	55	53	58	56	54	53	57	55	53	52	51
	横方向 (A)	縦方向 (B)	3.0	62	59	57	55	61	59	57	55	59	57	56	54	58	56	55	54	52
H m	1.17 H m	1.17 H m	4.0	63	61	60	58	62	61	59	58	61	59	58	57	59	58	57	56	55
			5.0	64	62	61	60	63	62	60	59	62	60	59	58	60	59	58	58	56
			7.0	65	64	63	62	64	63	62	61	63	62	61	60	61	60	60	60	59
			10.0	66	65	64	63	65	64	63	63	63	63	62	62	62	61	61	60	59

